



	<a href="#">NVR TC-R3105 SPEC: I/B/P4/K/V3.1.5 CHANNELS, 4 PoE TIANDY</a>	<a href="#">NVR DS-7104NI-Q1(C) 4 CHANNELS Hikvision</a>
		
	1724.00 PLN 1724.00 PLN	498.00 PLN 498.00 PLN
Standard	IP	TCP/IP
Supported resolutions	max. 8 Mpx	max. 4 Mpx - 2688 x 1520 px
Video outputs	1 pcs HDMI 4K 1 pcs VGA	1 pcs HDMI 1 pcs VGA
Audio support	5 Channels - Audio from cameras	4 Channels - Audio from cameras
Audio inputs	1 pcs	—
Audio outputs	1 pcs	—
Image compression method	S+265 / H.265 / S+264 / H.264	H.265+ / H.265 / H.264+ / H.264
Supported hard drives	1 x 10 TB SATA	1 x 6 TB SATA
Recording modes	Manual, Motion Detection, Schedule	Manual, Motion Detection, Schedule
Network protocols	...	TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, UPnP
External storage devices backup	Backup to USB drive (pendrive, external drive)	Backup to USB drive (pendrive, external drive)
Searching and playback the records	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) 1/4 channel synchronous playback	Records searching: by time and events type. Records playback: forward, backward, fast, slow
Network interface	1 x RJ-45 - 10 / 100 Mbps	...
Network functions	Full support via network, Remote records copying, Web-Server built-in	Live image view, Playback the records, Backup the records - iVMS-4200 application
ONVIF	✓	✓
Bitrate	max. 80 Mbps	max. 40 Mbps
Default admin user / password	admin / - The administrator password should be set at the first start	admin / - The administrator password should be set at the first start
Default IP address	192.168.1.3	192.168.1.168
Web browser access ports	80, 433, 3000, 3001, 3002, 23002	80
RTSP URL	rtsp://user:password@192.168.1.3:554/1/1 - Main stream rtsp://user:password@192.168.1.3:554/1/2 - Sub stream	• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
PC client access ports	3000, 3001	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	3000, 3001	8000

Mobile phones support	Port no.: 3000 or access by a cloud (P2P) • Android: Free application <a href="#">EasyLive Plus</a> • iOS (iPhone): Free application <a href="#">EasyLive Plus</a>	Port no.: 8000 or access by a cloud (P2P) • Android: Free application <a href="#">Hik-Connect</a> • iOS: Free application <a href="#">Hik-Connect</a>
Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application <a href="#">Easy7 Smart Client Express</a>	...
Alarm inputs / outputs	4 / 1	—
PTZ control	✓	IP Speed Dome Cameras
Operation temp	...	-10 °C ... 55 °C
Motion Detection	✓	✓
Intelligent image analysis	—	✓
USB	2 x USB 2.0	2 pcs USB 2.0
Mouse support	✓	✓
IR remote controller in the set	—	—
Main features	Support for Intelligent Image Analysis function, available in TIANDY cameras : • crossing the line (tripwire) • double crossing the line • abandoned/missing object • detection of loitering in a given area • running • parking detection • detection of people gathering • protective helmet detection • detection of persons on duty • signal loss indication • detection of persons on duty • people counting • face detection	...
Switch PoE	4-port PoE Switch built-in, 30 W / Channel - PoE	...
Maximum total switch load	45 W	...
Power supply	48 V DC / 1.35 A (power adapter included)	12 V DC / 1.5 A (power adapter included)
Weight	0.91 kg	0.42 kg
Dimensions	255 x 240 x 45 mm	197 x 203 x 48 mm
Country of origin	...	China
SAP Code	...	303613783
Supported languages	Polish, English, Albanian, Arabic, Spanish, Korean, French, Hebrew, Dutch, Portuguese, German, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand	TIANDY	Hikvision
Guarantee	3 years	3 years