




	NVR NVR4232-EI 32 CHANNELS WizSense DAHUA	MOUNTING PLATE BM-130X160	POLE MOUNT OR-100/S
			
	2052.00 PLN 2052.00 PLN	39.60 PLN 39.60 PLN	31.68 PLN 31.68 PLN
Standard	TCP/IP
Supported resolutions	max. 16 Mpx - 4608 x 3472 px
Pole diameters range	...	Ø 43 mm ... Ø 200 mm	Ø 38 ... Ø 100 mm
Video outputs	1 pcs HDMI 4K 1 pcs VGA
Montage hole diameter	9.7 mm
Material	...	Steel - Hot-dip galvanized + powder painting	Steel galvanized
Mounting holes distance	113 mm
Color	...	White	Silver
Cable hiding	—
Audio support	<ul style="list-style-type: none"> • 32 Channels - Audio from cameras • Bi-directional audio streaming support
Audio inputs	1 pcs CINCH
Audio outputs	1 pcs CINCH
Image compression method	Smart H.265+ / H.265 / Smart H.264+ / H.264 / MJPEG
Bitrate	max. 256 Mbps
Supported hard drives	2 x 16 TB SATA
Recording modes	Manual, Sensor, Motion detection, Schedule
External storage devices backup	Backup to USB drive (pendrive, external drive)
Searching and playback the records	<ul style="list-style-type: none"> • Records searching: by time and events type. Records playback: forward, backward, fast, slow • Advanced searching (to the one second accuracy) • Smart Playback function • Records playback from max. 16 channels in the same time @ 1080p (without AI) • Records playback from max. 12 channels in the same time @ 1080p (AI)
Network interface	1 x RJ-45 10/100/1000 Base-TX
Network functions	Full support via network, Remote records copying, Web-Server built-in
Network protocols	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search, P2P, Auto Register
ONVIF	22.06
Default IP address	192.168.1.108
Default admin user / password	admin / - The administrator password should be set at the first start
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application
Web browser access ports	80, 37777
PC client access ports	37777
Mobile client access ports	37777

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

RTSP URL	<ul style="list-style-type: none"> • rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream • rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
USB	2 pcs USB 2.0
Serial ports	—
Alarm inputs / outputs	4 / 2
PTZ control	IP Speed Dome Cameras
Motion Detection	✓
Intelligent image analysis	✓
Main features	<ul style="list-style-type: none"> • Intelligent image analysis : crossing the line (tripwire), intrusion, scene changing, face detection • SMD PLUS - searching for an object classified as: human, motor vehicle • Filtering of false alarms based on the recognition of persons and vehicles • Quick Pick - AI technology enabling, together with the recorder, quick identification of interesting objects (people/vehicles) based on an artificial intelligence algorithm. It allows to extract and compare the colors of clothes and vehicles • Face recognition • Face analysis: determination of sex, age and characteristic elements of appearance (glasses, facial hair, mask) • Support for up to 10 face databases, including 20 000 face images • In the base other than face photography, can also be stored such information as: name, sex, date of birth, nationality, address, ID number • Intelligent face search by metadata of different targets or uploading pictures of faces to the device and comparing them with recorded faces by similarity • Privacy zones <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none"> • ANPR • people counting • heat map
Mouse support	✓
IR remote controller in the set	—
Power supply	12 V DC / 4 A (power adapter included)
Power consumption	max. 10 W (without HDD)
Operation temp	-10 °C ... 55 °C
Weight	1.49 kg	0.4 kg	1 kg
Dimensions	375 x 284 x 53 mm	158 x 130 x 32 mm	...
Supported languages	Polish, English, Bulgarian, Czech, Finnish, Greek, Romanian, Serbian, Slovenian, Hungarian
Manufacturer / Brand	DAHUA	...	DELTA
Guarantee	3 years	2 years	3 years