



	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-T2A21-0280B - 1080p 2.8 mm DAHUA</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL VANDALPROOF CAMERA DS-2CE56D8T-ITMF(2.8MM) - 1080p Hikvision</a>
		
	227.00 PLN 227.00 PLN	323.00 PLN 323.00 PLN
Standard	HD-CVI, HD-TVI, AHD, PAL	AHD / HD-CVI / HD-TVI / CVBS
Sensor	1/2.7 " Progressive Scan CMOS	Progressive Scan CMOS
Matrix size	2.1 Mpx	2.1 Mpx
Resolution	1920 x 1080 - 1080p , 1280 x 720 - 720p , 960 x 576 - 960H, PAL	• 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI • 960 x 576 - 960H @ PAL
Range of IR illumination	20 m	30 m
IR illuminator power adjustment	Automatic	Automatic
Lens	2.8 mm	2.8 mm
IR illuminator support	...	ICR - Movable InfraRed filter
View angle	• 103 ° (manufacturer data) • 100 ° (our tests result)	• 104 ° (manufacturer data) • 101 ° (our tests result)
S/N ratio	> 65 dB	> 62 dB
Video output	HD-CVI / HD-TVI / AHD / PAL, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio	—	...
Main features	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• AGC - Automatic Gain Control</li> <li>• ICR - Movable InfraRed filter</li> <li>• Mirror - Mirror image</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> </ul>	<ul style="list-style-type: none"> <li>• WDR ≥ 130 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• AGC - Automatic Gain Control</li> <li>• BLC - Back Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> </ul>

OSD menu	OSD menu available via DAHUA recorder	OSD menu available via recorder
Power supply	12 V DC / 220 mA	12 V DC / 280 mA
Power consumption	≤ 2.7 W	≤ 3.4 W
Housing	Dome, Aluminum	Dome, Metal
Color	White	White
Vandal-proof	—	—
"Index of Protection"	IP67	IP67
Operation temp	-40 °C ... 60 °C	-40 °C ... 60 °C
Weight	0.27 kg	0.24 kg
Dimensions	Ø 94 x 78 mm	91 x 83 x 68 mm
SAP Code	...	300612680
Supported languages	Polish, English, French, Spanish, German, Portuguese, Russian, Italian	...
Manufacturer / Brand	DAHUA	Hikvision
Guarantee	3 years	3 years