



| | | |
|--------------------------|---|---|
| | IP CAMERA IPC2124LE-ADF40KM-G - 4 Mpx 4 mm UNIVIEW | STRAIGHT SOCKET LE-50112 230 V 16 A LEGRAND |
| |  |  |
| | 642.51 PLN 642.51 PLN | 104.68 PLN 104.68 PLN |
| Standard | TCP/IP | ... |
| Sensor | 1/3 " Progressive Scan CMOS | ... |
| Rated voltage | ... | 230 V / 50 Hz |
| Matrix size | 4 Mpx | ... |
| Maximal current load | ... | 16 A |
| Grounding | ... | ✓ |
| Electrical cable | ... | max. 3 x 2.5 mm ² |
| Cable terminals | ... | automatic spring terminals |
| Socket type | ... | CEE 7/5 |
| IK rating | ... | IK08 |
| Resolution | 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p | ... |
| Lens | 4 mm | ... |
| View angle | • 84 ° (manufacturer data) • 80 ° (our tests result) | ... |
| Range of IR illumination | 50 m | ... |
| S/N ratio | > 52 dB | ... |
| RS-485 interface | — | ... |
| Memory card slot | Micro SD memory cards up to 256GB support (possible local recording) | ... |
| Image compression method | Ultra 265 / H.265 / H.264 / MJPEG | ... |
| Alarm inputs / outputs | — | ... |
| Audio | • Microphone built-in • Audio transmission via network • Audio detection | ... |
| Main stream frame rate | 25 fps @ 4 Mpx | ... |
| Network interface | 10/100 Base-T (RJ-45) | ... |
| Network protocols | IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL / TLS, QoS, IEEE 802.1x, SNMP | ... |
| WEB Server | Built-in | ... |

| | | |
|-------------------------------|--|-------|
| Max. number of on-line users | 32 | ... |
| ONVIF | ✓ | ... |
| Mobile phones support | Access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView | ... |
| Default IP address | DHCP or 192.168.1.13 | ... |
| Default admin user / password | admin / 123456 | ... |
| Web browser access ports | 80, 554 | ... |
| PC client access ports | Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation | ... |
| Mobile client access ports | 80 | ... |
| Port ONVIF | 80 | ... |
| RTSP URL | rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream | ... |
| Main features | <ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines • Intelligent image analysis : intrusion, crossing the line (tripwire) (human silhouette) | ... |
| Power supply | • PoE (802.3af), • 12 V DC / 540 mA | ... |
| Power consumption | ≤ 6.5 W | ... |
| Housing | Compact, Metal + Plastic | ... |
| Color | White | Black |
| "Index of Protection" | IP67 | IP44 |

| | | |
|----------------------|--|---------------|
| Vandal-proof | — | ... |
| Operation temp | -30 °C ... 60 °C | ... |
| Weight | 0.43 kg | 0.084 kg |
| Dimensions | 190 x 73 x 71 mm | Ø 56 x 115 mm |
| Supported languages | Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian | ... |
| Manufacturer / Brand | UNIVIEW | LEGRAND |
| Guarantee | 3 years | 2 years |