



	<a href="#">SWITCH POE IP-5-11-E 5-PORT ATTE</a>	<a href="#">RFID PROXIMITY CARD ATLO-307 13.56 MHz S50</a>
		
	529.00 PLN 529.00 PLN	2.01 PLN 2.01 PLN
LAN ports	<ul style="list-style-type: none"> <li>• 1 x RJ45 10/100 Base-T - Uplink</li> <li>• 5 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE</li> </ul>	...
Standard	...	13.56 MHz S50
Compatibility	...	ISO/IEC 14443A
Possibility of programming the serial number (ID)	...	—
Management	—	...
Ability to write to internal memory	...	1 kB
Serial Number overprint	...	—
LED diodes	Power, LAN	...
Transmission speed	10 / 100 Mbps : 1 Port LAN + 5 LAN & PoE ports	...
Maximal output power	<ul style="list-style-type: none"> <li>• 40 W @ Passive PoE - 1 ... 4 ports,</li> <li>• 70 W @ Passive PoE - Port 5,</li> <li>• 30 W @ PoE (802.3af/at) - 1 ... 5 ports</li> </ul>	...
Maximal total power	96 W	...
Operation modes	<ul style="list-style-type: none"> <li>• Normal : 100 m @ 10/100 Mb/s - 1 ... 5 ports</li> <li>• Long Range : 280 m @ 10 Mb/s - 1 ... 4 ports ; 100 m @ 10/100 Mb/s - Port 5</li> <li>• Port LAN 6 - Uplink</li> </ul>	...

Main features	<ul style="list-style-type: none"> <li>• Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port)</li> <li>• The output PoE voltage is equal to the input voltage</li> <li>• The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports</li> <li>• The modular design streamlines service tasks and enables quick and easy system expansion</li> <li>• The raster system of module assembly facilitates the expansion of the device by further modules</li> </ul>	Range : ~ 10 cm ,
Power supply	230 V AC - cable terminals	...
Weight	1.4 kg	0.005 kg
Dimensions	255 x 205 x 95 mm	86 x 54 x 0.8 mm
Manufacturer / Brand	ATTE	ATLO
Guarantee	3 years	2 years