

	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1500CLO-IL-A-0280B-S2 - 5 Mpx 2.8 mm DAHUA	ADAPTER IEC320/2XGS
		
	83.27 USD 83.27 USD	7.21 USD 7.21 USD
Standard	AHD, HD-CVI, HD-TVI, CVBS	...
Sensor	Progressive Scan CMOS	...
Connector type	...	Adapter Plug IEC320 / 2 x Power socket CEE 7/5
Matrix size	5 Mpx	...
Voltage	...	max. 250 V
Current	...	max. 16 A
Material	...	PET
Main features	...	<ul style="list-style-type: none"> • Very easy and quick assembly • Corrosion resistance
Length of the cable	...	0.2 m
Resolution	2880 x 1620 - 5 Mpx @ HD-CVI @ 25 fps - Aspect Ratio 16 : 9 , 2560 x 1440 - 3.7 Mpx @ HD-CVI / HD-TVI / AHD @ 25 fps , 1920 x 1080 - 1080p @ HD-CVI @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps	...
Lens	2.8 mm	...
View angle	<ul style="list-style-type: none"> • 106 ° (manufacturer data) • 100 ° (our tests result) 	...
Range of IR illumination	20 m	...
White light LED illuminator range	20 m	...
IR illuminator power adjustment	Automatic	...
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...
Audio	<ul style="list-style-type: none"> • Microphone built-in, • Audio support via coaxial cable - HD-CVI only 	...
OSD menu	✓	...

Main features	<ul style="list-style-type: none"> • Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • Auto White Balance • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • BLC/HLC - Back Light / High Light Compensation • Privacy zones - max. 8 • Mirror - Mirror image • Sharpness - sharper image outlines 	...
Power supply	12 V DC / 380 mA	...
Power consumption	≤ 4.5 W	...
Housing	Dome, Plastic	...
Color	White	...
"Index of Protection"	IP67	...
Vandal-proof	—	...
Operation temp	-40 °C ... 60 °C	...
Weight	0.21 kg	0.130 kg
Dimensions	Ø 97 x 94 mm	...
Manufacturer / Brand	DAHUA	...
Guarantee	3 years	2 years