



	<a href="#">EXTENDER USB-EX-150/4-USB</a>	<a href="#">PLUG F/6.5E*P100</a>
		
	258.77 PLN 258.77 PLN	33.00 PLN 33.00 PLN
In package	...	<b>100 pcs The price for package</b>
Connector type	...	"F" Straight plug
Attachment of connector elements	...	Twisted-on
Shield fastening	...	Twisting-on
Connectors	<ul style="list-style-type: none"> <li>• Transmitter :</li> <li>- 1 x USB-A</li> <li>- 1 x RJ-45 shielded socket</li> <li>• Receiver :</li> <li>- 4 x USB-A</li> <li>- 1 x RJ-45 shielded socket</li> </ul>	...
Wire mounting	...	—
Application	...	Coaxial cable
Cable diameter	...	max. 6.5
Impedance	...	75 Ω
Material	...	Metal
Range	<ul style="list-style-type: none"> <li>• 150 m - USB 2.0 @ UTP cat. 6,</li> <li>• 100 m - USB 2.0 @ UTP cat. 5e</li> </ul>	...
UTP category	5e / 6 / 6A / 7	...

Main features	<ul style="list-style-type: none"> <li>• USB 2.0 - High-Speed (480 Mb/s) (compatible with older)</li> <li>• Supports 4 USB 2.0 inputs and 1 USB 2.0 output</li> <li>• The transmitter is powered from the source device - no additional power supply is required</li> <li>• The device supports a cascade of gigabit switches, which allows to increase the transmission distance</li> <li>• Lightning protection, surge protection, ESD protection</li> <li>• Easy installation - Plug&amp;Play USB device type</li> </ul>	<ul style="list-style-type: none"> <li>• Wide frequency range</li> <li>• Corrosion resistance</li> </ul>
Power supply	5 V DC / 1 A (power adapter included) - Receiver	...
Operation temp	-20 °C ... 60 °C	...
Housing	Metal	...
Weight	0.12 kg	0.005 kg
Dimensions	77 x 61 x 21 mm	Ø 11 mm x 20 mm
Guarantee	2 years	2 years