



	<a href="#">POLE MOUNT USH-M3</a>	<a href="#">SWITCH POE CS4010-8GT-110 8-PORT DAHUA</a>
		
	109.51 PLN 109.51 PLN	1124.00 PLN 1124.00 PLN
Support	SH-750/595/322	...
Material	Magnelis - carbon steel, coated with a zinc- aluminum-magnesium alloy	...
Number of fastening elements	3	...
Mast diameter	Ø 50 mm (max)	...
Plate thickness	2 mm	...
Mounting holes distance	• 165 mm, • 510 mm	...
LAN ports	...	• 8 x RJ45 10/100/1000 Base-T ( 1 x Hi-PoE (802.3bt) + 7 x PoE (802.3af/at) ), • 2 x RJ45 10/100/1000 Base-T - Uplink
Transmission speed	...	• 10 / 100 / 1000 Mbps : 8 LAN & PoE ports, • 10 / 100 / 1000 : 2 Uplink ports
Maximal output power	...	• 90 W / port Hi-PoE / PoE 802.3bt - Port 1 • 30 W / port PoE 802.3af/at - 2 ... 8 ports
Maximal total power	...	110 W
MAC addresses table	...	8k
Management	...	✓
Operation modes	...	Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6
LED diodes	...	Power, System, PoE, Link/Act

Main features	Mounting to the mast with u-bolts	<ul style="list-style-type: none"> <li>• Switch is managed through the web and the cloud (DoLynk Care application)</li> <li>• PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-)</li> <li>• Intelligent management of Power Supply Unit power's output stage</li> <li>• protection against lightning discharges and voltage differences and strokes between devices</li> <li>• Watchdog PoE</li> <li>• Loop Protection</li> <li>• Compliance with the LLDP protocol</li> <li>• Spanning Tree STP/RSTP</li> <li>• Port Based VLAN : 32</li> <li>• Data Flow Control (802.3x)</li> <li>• DHCP client</li> <li>• RESET button</li> <li>• Possibility to mount to the wall</li> </ul>
Certificates	...	CE
Protections	...	<ul style="list-style-type: none"> <li>• Protection against lightning discharges (common/differential) : 4 / 2 kV</li> <li>• Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV</li> </ul>
Housing	...	Desktop, Metal
Power supply	...	54 V DC / 2.22 A (power adapter included)
Power consumption	...	max. 110 W
Operation temp	...	-10 °C ... 55 °C
Weight	2.04 kg	0.52 kg
Dimensions	...	190 x 106 x 30 mm
Manufacturer / Brand	...	DAHUA
Guarantee	2 years	3 years