

	LASER RANGEFINDER LM-70A UNI-T	POWER DISTRIBUTION UNIT ACAR-ECO-PLUS (6 OUTLETS)	ACCESS CONTROLLER MODULE MC16-PAC-EX-2 ROGER
			
	102.65 PLN 102.65 PLN	242.26 PLN 242.26 PLN	2130.00 PLN 2130.00 PLN
Maximal load power	...	2300 W	...
Number of served transitions	...	...	2
Measurement range	70 m $\pm$ (2mm+5x10 ⁻⁵ D)	...	...
Inputs	...	...	12
Continuous measurement	✓	...	...
Nominal voltage	...	230 V AC / 50 Hz	...
Outputs	...	...	8
Area measurement	✓	...	...
Volume measurement	✓	...	...
Fuse	...	10 A / 250 V	...
Number of users	...	...	max. 12000 - Number of identifiers
Measurement of the cathetus	✓	...	...
Switch	...	two-way	...
Measurements using the Pythagorean theorem	✓	...	...
Leak current	...	< 0.5 mA	...
Number of media per ID	...	...	8 - Proximity card, PIN code, fingerprint, etc.
Section measurement	✓	...	...
Response time	...	< 25 ns	...
Number of permissions per ID	...	...	100
Angle measurement	—	...	...
Nominal voltage of surge suppressor	...	250 V	...
Buffer memory	...	...	8 000 000 events buffer
Measurement of deviation from the level	—	...	...
Protection level	...	1.3 kV (L/N)	...
MCT readers support	...	...	16 pcs
Measurement of deviation from the vertical	—	...	...
Add/subtract function	✓	...	...
Nominal stroke current	...	2 kA (L/N) - (8/20μs)	...

Save measurements	99 groups	...	...
Readers connections	...	...	4 pcs - Wiegand / PRT
Number of login points	...	...	4
Maximum stroke current	...	6.5 kA (L/N) - (8/20µs)	...
Number of access terminals	...	...	8
Electric shock protection system	...	Ground connectors (pins) connected with ground wire of AC mains	...
Housing	...	Plastic - non-flammable	...
Number of access zones	...	...	4
Measurement unit	meters / feet / inches	...	...
Number of alarm zones	...	...	4
Number of automation nodes	...	...	4
Number of output outlets	...	• 1 MASTER outlet, two-contact with ground contact • 3 SLAVE outlets with auto switch off the power supply after switch off the receiver powered from MASTER outlet • 2 outlets separate from MASTER outlet	...
Length of the cable	...	1.45 m	...
Battery backup support	...	...	12 V / 7 Ah
Communication	...	...	• Ethernet - RJ-45 socket • RS-485 interface • RACS 5 v2 (Roger)
Main features	• Reference point: front or back of the device • LCD display 2 " - White backlight • Battery charge indicator • Self-calibration function • Laser 630-670nm, <1mW • Automatically turns off the laser after 20 s • Automatically turns off the device after 3 min • Buzzer • Built-in mini spirit level - vertical/horizontal • The set includes a practical case	...	• Integrated support in VISO EX software • Functions in the VISO EX system: - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system - unlimited - division of the system into partitions operated by independent operators - tool for integration with RACS5 (API) systems - integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems)

Power supply	Alkaline batteries AAA, 2 pcs (included)	...	• 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC
Operation temp	0 °C ... 40 °C	...	5 °C ... 40 °C
Permissible relative humidity	...	...	10 % ... 95 % (non-condensing)
Weight	0.09 kg	0.56 kg	0.14 kg
Dimensions	112 x 50 x 25 mm	447 x 55 x 53 mm	175 x 72 x 30 mm
Manufacturer / Brand	UNI-T	...	ROGER
Guarantee	2 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00