

	<a href="#">VIDEO DOORPHONE VTO2111D-P-S3 DAHUA</a>	<a href="#">PLUG F/6.5*P10</a>
		
	868.00 PLN 868.00 PLN	7.50 PLN 7.50 PLN
Compatibility	DAHUA	...
Sensor	1/2.8 ", 2 Mpx CMOS	...
In package	...	<b>10 pcs The price for package</b>
View angle	107 °	...
Connector type	...	"F" Straight plug
Image compression method	H.265 / H.264	...
Attachment of connector elements	...	Twisted-on
IR illuminator	✓	...
Shield fastening	...	Twisting-on
Wire mounting	...	—
Application	...	Coaxial cable
Cable diameter	...	max. 6.5 ± 0.05 mm
Impedance	...	75 Ω
Material	...	Metal
Resolution	<ul style="list-style-type: none"> <li>• Main stream : 1280 x 720, 800 x 480, 720 x 576</li> <li>• Sub stream : 1920 x 1080, 800 x 480, 720 x 576, 352 x 288, 320 x 240</li> </ul>	...
proximity reader built-in	Access control cards - 13.56 MHz S50, Memory of 10 000 RFID cards	...
The number of subscribers served	1	...

Main features	<ul style="list-style-type: none"> <li>• It can only work with the mobile application, without the VTH monitor</li> <li>• The function of the monitor with the ability to open the door can be a smartphone, tablet or the VTH indoor panel</li> <li>• Motion Detection</li> <li>• D-WDR - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• Bidirectional communication,</li> <li>• Microphone built-in,</li> <li>• Speakers built-in,</li> <li>• Tamper detection - opening the enclosure,</li> <li>• Door contact and request button for exit inputs</li> </ul>	<ul style="list-style-type: none"> <li>• Wide frequency range</li> <li>• Corrosion resistance</li> </ul>
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">DMSS</a></li> <li>• iOS (iPhone): Free application <a href="#">DMSS</a></li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 1000 mA</li> </ul>	...
Power consumption	<ul style="list-style-type: none"> <li>• ≤ 1 W (Standby mode),</li> <li>• ≤ 5 W (operation)</li> </ul>	...
Housing	Plastic, Waterproof	...
Color	Graphite	...
"Index of Protection"	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	...
IK rating	IK04	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.16 kg	0.005 kg
Dimensions	135 x 71 x 35 mm	Ø 11 mm x 18 mm
Supported languages	Polish, English, Bulgarian, Czech, Finnish, Slovenian, Slovak, Hungarian	...
Manufacturer / Brand	DAHUA	...
Guarantee	3 years	2 years