



	ACCESS CONTROLLER ASC2202B-D DAHUA	POWER SUPPLY ADAPTER 12V/3A/5.5
		
	1109.00 PLN 1109.00 PLN	34.72 PLN 34.72 PLN
Model identifier	...	12V/3A/5.5
Number of served transitions	2 (two-way)	...
Support	DAHUA	...
Input voltage	...	100 - 240 V AC
Number of supported readers	4 pcs	...
Battery backup support	—	...
AC input frequency	...	50 / 60 Hz
Output voltage	...	12.0 V DC
Output lines	4 pcs - Relay	...
Output current	...	3.0 A
Output power	...	36.0 W
Average efficiency during work	...	87.4 %
Efficiency at low load (10%)	...	81.0 %
No-load power consumption	...	< 0.10 W
Communication	<ul style="list-style-type: none"> • RS-485, • Ethernet, • Wiegand 	...
Adapter type	...	Switching
Output voltage adjustment	...	—
Protections	...	Overload
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 1.4 A 	...
Number of outputs	...	1 pcs
Power connectors type	...	<ul style="list-style-type: none"> • 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug
Housing type	...	Desktop

Main features	<ul style="list-style-type: none"> • 100000 indexed users • History of 500000 events • Remote programming from PC • Function of protection against multiple use of the same card for access (anti-passback) • Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value • Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress • Possibility to mount on a wall, or on the DIN TS-35 rail 	...
Default IP address	192.168.0.2	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Operation temp	-30 °C ... 60 °C	...
Permissible relative humidity	max. 95 % (non-condensing)	...
Weight	0.4 kg	0.26 kg
Dimensions	210 x 106 x 50 mm	110 x 50 x 30 mm
Manufacturer / Brand	DAHUA	...
Guarantee	3 years	2 years