



	<a href="#">ROUTER CUDY-X6 Wi-Fi 6, 2.4 GHz, 5 GHz, 574 Mbps + 1201 Mbps</a>	<a href="#">IP CAMERA DS-2CD2T47G2H-LI(4MM)(EF) ColorVu - 4 Mpx Hikvision</a>
		
	204.88 PLN 204.88 PLN	1775.00 PLN 1775.00 PLN
Standard	...	TCP/IP
Frequency range	2.4 GHz, 5 GHz ,	...
Sensor	...	1/1.8 " Progressive Scan CMOS
Matrix size	...	4 Mpx
Antenna type	4 x Omnidirectional antenna 5 dBi - Integrated	...
Resolution	...	2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p
Standards	IEEE 802.11ax/n/b/g @ 2.4 GHz , IEEE 802.11ax/ac/n/a @ 5 GHz	...
Lens	...	4 mm
Baud rates	574 Mbps + 1201 Mbps	...
View angle	...	• 89 ° (manufacturer data) • 85 ° (our tests result)
White light LED illuminator range	...	60 m
Range of IR illumination	...	60 m
Memory card slot	...	Micro SD memory cards up to 512GB support (possible local recording)
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	—
LAN ports	1 x 10/100/1000 Mbps - WAN 4 x 10/100/1000 Mbps - LAN	...
Audio	...	—
Main stream frame rate	...	25 fps @ 4 Mpx
LED indicators	Power / System, LAN - Link/Act	...
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	6
ONVIF	...	19.12

Main features	...	<ul style="list-style-type: none"> <li>• Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• WDR - 130 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Horizontal mirror image</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Configurable Privacy Zones</li> <li>• Sharpness - sharper image outlines</li> <li>• video tampering</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, scene changing, detection of entry into the area / exit from the area - classification of people and vehicles, face detection</li> </ul>
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">Hik-Connect</a></li> <li>• iOS: Free application <a href="#">Hik-Connect</a></li> </ul>
Default IP address	...	192.168.1.64
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> <li>• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li> <li>• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/</li> </ul>
DDNS	✓	...
DHCP server	✓	...
Firmware update	✓	...
Protections	WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPA3	...
Power consumption	...	<ul style="list-style-type: none"> <li>• ≤ 9 W @ PoE</li> <li>• ≤ 8 W @ 12 V DC</li> </ul>

Management interface	Web browser	...
Housing	...	Compact, Metal
Color	...	White
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-30 °C ... 60 °C
Operation modes	<ul style="list-style-type: none"> <li>• Router,</li> <li>• AP,</li> <li>• Range Extender,</li> <li>• WISP</li> </ul>	...
Transmitter power	<ul style="list-style-type: none"> <li>&lt; 20 dBm @ 2.4 GHz</li> <li>&lt; 23 dBm @ 5 GHz</li> </ul>	...
Power supply	12 V DC / 1.5 A (power adapter included)	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 660 mA</li> </ul>
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
SAP Code	...	311323651
Main features	<ul style="list-style-type: none"> <li>• Support for CUDY Whole Home Mesh technology</li> <li>• Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments</li> <li>• WPS/RESET button</li> <li>• The WPS function allows to easy establish an encrypted connection</li> <li>• Built-in 4-port switch</li> <li>• WMM (Wi-Fi Multimedia)</li> <li>• WAN : Fixed, or dynamic IP address, PPPoE</li> <li>• DHCP : DHCP server, DHCP client list, address reservation</li> <li>• Guest Network - a separate and secure network for guests</li> <li>• parental control</li> <li>• NAT : Port forwarding, Port Triggering, UPnP, DMZ</li> <li>• VPN networks: PPTP, L2TP, OpenVPN, WireGuard, IPSec, Zerotier</li> <li>• Access control</li> <li>• Remote management</li> <li>• VLAN</li> <li>• IPTV compliance</li> <li>• IPv6 compliance</li> </ul>	...
Weight	0.37 kg	1.12 kg



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Dimensions	205 x 138 x 38 mm	287 x 93 x 91 mm
Manufacturer / Brand	CUDY	Hikvision
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00