



	IP CAMERA F4C-PV Wi-Fi, Smart Dual Light Active Deterrence - 3.7 Mpx 2.8 mm DAHUA	SLOTTED SCREWDRIVER 5.5 ST-STHT0-60389 STANLEY
		
	189.00 PLN 189.00 PLN	13.93 PLN 13.93 PLN
Standard	IP	...
Tip size	...	5.5 mm
Arrowhead length	...	100 mm
Voltage insulation	...	—
Main features	...	<ul style="list-style-type: none"> • High-quality chrome-vanadium steel bar protects against corrosion and reduces the chance of tip breakage • Ergonomically designed bi-material handle reduces fatigue, improves efficiency • Large diameter handle offers great torque
Resolution	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	...
Sensor	1/3 " Progressive Scan CMOS	...
Lens	2.8 mm	...
View angle	98 °	...
Range of IR illumination	30 m	...
White light LED illuminator range	30 m	...
S/N ratio	> 56 dB	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Image compression method	H.265+ / H.265 / H.264+ / H.264	...
Alarm inputs / outputs	—	...
Audio	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in, • Bi-directional audio streaming support • Audio output • Audio detection 	...
Main stream frame rate	25 fps @ 4 Mpx	...
Network interface	<ul style="list-style-type: none"> • Wi-Fi - IEEE 802.11 b/g/n, 2.4 GHz, • 10/100 Base-T (RJ-45) 	...
WEB Server	Built-in	...
Max. number of on-line users	6	...
ONVIF	✓	...

Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	...
Default IP address	192.168.1.108	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Main features	<ul style="list-style-type: none"> • Active deterrence function • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Image rotation and mirror • Motion Detection - max. 4 configurable zones - Human detection • Privacy zones - max. 4 	...
Power supply	12 V DC / 550 mA	...
Power consumption	≤ 6.6 W @ 12 V DC	...
Housing	Compact - Plastic	...
Color	White + Black	...
"Index of Protection"	IP67	...
Vandal-proof	—	...
Operation temp	-40 °C ... 60 °C	...
Weight	0.25 kg	0.082 kg
Dimensions	131 x 78 x 97 mm	Ø 32 x 195 mm
Supported languages	Polish, English	...
Manufacturer / Brand	DAHUA	STANLEY
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00