




	IP HYBRID THERMAL IMAGING CAMERA TC-C35LQ SPEC:I5W/E/Y/T/6MM/V4.2 6.8 mm - 720p, - 5 Mpx 6 mm TIANDY	BATTERY DS-2FSCH30 FOR THE DS-2XS6A87G1-L/C32S80 CAMERA 10.8 V Hikvision	MEMORY CARD SD-10/32-SAND UHS-I, SDHC 32 GB SANDISK
			
	6631.00 PLN 6631.00 PLN	4348.00 PLN 4348.00 PLN	33.96 PLN 33.96 PLN
Rated voltage	...	10.8 V	...
Type	SD (Secure Digital)
Battery capacity	...	30 Ah	...
Pixel pitch	12 µm
Type	UHS-I, SDHC
Application	...	DS-2XS6A87G1-L/C32S80	...
Capacity	32 GB
Read speed	120 MB/s
Maximal output current	...	8 A	...
Thermal sensitivity (NETD)	< 55 mK @ F1.1
Battery charging voltage	...	max. 12.6 V	...
Class	10, U1
Spectral range	8 µm ... 14 µm
Main features	...	<ul style="list-style-type: none"> • Built-in MPPT batteries solar charge controller • RS-485 control 	...
Type (size)	...	255 x 172 x 80 mm	...
Resolution	1280 x 720 px - 720p , 704 x 576 px , 640 x 480 px , 352 x 288 px 2880 x 1620 - 5 Mpx 2688 x 1520 - 4 Mpx 2560 x 1440 - 3.7 Mpx 2304 x 1296 - 3 Mpx
Sensor	Uncooled VOx microbolometer 1/2.7 " Progressive Scan CMOS
Lens	6.8 mm 6 mm
View angle	26 ° 53 °
Range of IR illumination	50 m

Standard	IP
Video output	—
RS-485 interface	✓
Memory card slot	Micro SD card support up to 512GB
Image compression method	S+265 / H.265 / H.264
Alarm inputs / outputs	2 / 1
Audio	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in • Audio input • Bi-directional audio streaming support • Audio output
Main stream frame rate	<ul style="list-style-type: none"> • 25 fps @ 1280 x 960 • 25 fps @ 5 Mpx
Interface	10/100 Base-T (RJ-45)
WEB Server	Built-in
Max. number of on-line users	3
ONVIF	✓
Mobile phones support	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus
Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express
Default IP address	DHCP or 192.168.1.2
Default admin user / password	admin / - The administrator password should be set at the first start
Web browser access ports	80, 443, 3000, 3001, 3002, 23002
Mobile client access ports	3000, 3001
PC client access ports	3000, 3001
Port ONVIF	80

Intelligent image analysis	<ul style="list-style-type: none"> • crossing the line (tripwire) • double crossing the line • classification of people and vehicles • intrusion
Main features	<ul style="list-style-type: none"> • WDR - Wide Dynamic Range • ROI - improve the quality of selected parts of image • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Day/Night mode (color/b&w/auto) • Auto White Balance • AGC - Automatic Gain Control • Sharpness - sharper image outlines • Motion Detection • Detection of people smoking cigarettes • High temperature indication
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC
Power consumption	≤ 9 W
Housing	Compact - Metal	Aluminum	...
Color	White	White	...
"Index of Protection"	IP67	IP68	...
Operation temp	-35 °C ... 65 °C
Weight	1.47 kg	3.4 kg	...
Dimensions	327 x 115 x 109 mm	...	32 x 24 x 2 mm
Supported languages	Polish, Albanian, English, Arabic, Spanish, French, Hebrew, Dutch, Korean, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian
Manufacturer / Brand	TIANDY	Hikvision	SANDISK
Guarantee	3 years	2 years	2 years