



	<a href="#">ANTENNA IMPEDANCE TRANSFORMER SA/III-V-DIPOL</a>	<a href="#">SWITCH TL-SG3428X 24-PORT SFP TP-LINK</a>
		
	5.90 PLN 5.90 PLN	1278.51 PLN 1278.51 PLN
Receiving channels	6 ... 48	...
LAN ports	...	<ul style="list-style-type: none"> <li>• 24 x RJ45 10/100/1000 Base-TX,</li> <li>• 4 x port SFP+ - Uplink 1000 Base-X / 10 Gigabit Ethernet,</li> <li>• 1 x RJ45 - Console,</li> <li>• 1 x micro USB - Console</li> </ul>
Management	...	✓
Transmission speed	...	<ul style="list-style-type: none"> <li>• 10 / 100 / 1000 Mbps - 24 LAN ports,</li> <li>• 10 Gb/s - 4 SFP ports</li> </ul>
Jumbo Frame	...	9 kB
MAC addresses table	...	16k

Main features	...	<ul style="list-style-type: none"> <li>• Omada Central Management System</li> <li>• Software Omada Controller</li> <li>• Switch is managed via a web browser, command line interface and SNMP, RMON protocols</li> <li>• CoS/DSCP priority based on IEEE 802.1p standard</li> <li>• Queue scheduling: SP, WRR, SP+WRR</li> <li>• Port/flow-based rate limiting</li> <li>• Static link aggregation</li> <li>• Spanning Tree STP/RSTP/MSTP</li> <li>• BPDU Filtering/Guard</li> <li>• TC / Root Protect</li> <li>• Loop back detection</li> <li>• Data Flow Control (802.3x)</li> <li>• Port mirroring function</li> <li>• IGMP Snooping V1/V2/V3</li> <li>• IEEE 802.1Q VLAN, Port Based VLAN, MAC Based VLAN, Private VLAN support</li> <li>• IEEE 802.1Q standard support, up to 4096 VLAN groups and 4K VIDs</li> <li>• GVRP (GARP VLAN Registration Protocol) support</li> <li>• Access Control List - ACL package filtering based on source and destination MAC addresses</li> <li>• Hardware supports IP + MAC binding based on port</li> <li>• DHCP snooping support</li> <li>• Support DoS defence</li> <li>• Storm Control function</li> <li>• IEEE 802.1x and Radius Authentication</li> <li>• Port isolation</li> <li>• SSL, SSH</li> <li>• IPv6 compliance</li> <li>• Multicast</li> <li>• Static routing</li> <li>• DHCP server</li> <li>• DHCP client</li> <li>• Group control</li> <li>• Reboot schedule</li> <li>• MIB support</li> <li>• Console : RJ-45 output, micro USB</li> </ul>
---------------	-----	---



LED diodes	...	Power, System, Link/Act, 1000 Mbps Speed, 10 Gb/s Speed - 25 ... 28 ports
Housing	...	Metal
Operation temp	...	0 °C ... 45 °C
Certificates	...	CE, FCC, RoHS
Power supply	...	100 ... 240 V AC
Power consumption	...	max. 23.6 W @ 110 V
Weight	0.013 kg	2 kg
Dimensions	47 x 41 x 10 mm	440 x 180 x 44 mm, RACK 19", 1U
Manufacturer / Brand	...	TP-LINK
Guarantee	2 years	5 years