




	IP CAMERA DS-2CD1347G0-L(2.8mm)(C) ColorVu 4 Mpx Hikvision	IP CAMERA IPC3614LE-ADF28KC-WL ColorHunter - 4 Mpx 2.8 mm UNIVIEW
		
	887.00 PLN 887.00 PLN	690.00 PLN 690.00 PLN
Standard	TCP/IP	TCP/IP
Sensor	1/3 " Progressive Scan CMOS	1/3 " Progressive Scan CMOS
Matrix size	4 Mpx	4 Mpx
Resolution	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p
Lens	2.8 mm	2.8 mm @ F1.6
View angle	<ul style="list-style-type: none"> • 97 ° (manufacturer data) • 93 ° (our tests result) 	<ul style="list-style-type: none"> • 113 ° (manufacturer data) • 97 ° (our tests result)
White light LED illuminator range	30 m	30 m
Range of IR illumination	...	30 m
S/N ratio	...	> 52 dB
RS-485 interface	...	—
Memory card slot	—	Micro SD memory cards up to 128GB support (possible local recording)
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	—	—
Audio	—	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in • Bi-directional audio streaming support • Audio transmission via network • Audio detection
Main stream frame rate	20 fps @ 4 Mpx , 25 fps @ 1080p	25 fps @ 4 Mpx
Network interface	10/100 Base-T (RJ-45)	10/100 Base-TX (RJ-45)
Network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, IEEE 802.1x, QoS, IPv4/IPv6, Bonjour, UDP, SSL / TLS	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL / TLS, IEEE 802.1x, SNMP
WEB Server	Built-in	Built-in
Max. number of on-line users	6	32
ONVIF	18.12	✓
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect 	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address	192.168.1.64	DHCP or 192.168.1.13
Default admin user / password	admin / - The administrator password should be set at the first start	admin / 123456

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Web browser access ports	80	80, 554
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	8000	80
Port ONVIF	80	80
RTSP URL	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ 	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream
Main features	<ul style="list-style-type: none"> • Possibility to turn off the LED illuminator • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • BLC - Back Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Motion Detection • Configurable Privacy Zones • Sharpness - sharper image outlines 	<ul style="list-style-type: none"> • ColorHunter - colorful night mode • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • WB - White Balance (ATW/AWB/manual/indoor/outdoor) • Day/Night mode (color/b&w/auto) • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • Possibility to change the resolution, quality and bit rate • Sharpness - sharper image outlines • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Intelligent image analysis : crossing the line (tripwire), intrusion (human silhouette) • Overvoltage protection : 4 kV
SAP Code	311316796	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 400 mA 	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 670 mA
Power consumption	<ul style="list-style-type: none"> ≤ 6.5 W @ PoE ≤ 5 W @ 12 V DC 	≤ 8 W
Housing	Dome, Aluminum + Plastic	Dome, Metal + Plastic
Color	White	White


DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

"Index of Protection"	IP67	IP67
Vandal-proof	—	IK10
Operation temp	-30 °C ... 60 °C	-30 °C ... 60 °C
Weight	0.39 kg	0.31 kg
Dimensions	Ø 110 x 104 mm	Ø 118 x 96 mm
Supported languages	English, Ukrainian	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian
Manufacturer / Brand	Hikvision	UNIVIEW
Guarantee	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00