



	OVERVOLTAGE LIMITER AXON-POE-MULTINET-12	UPS VI-750/R1U 750 VA PowerWalker
		
	849.77 PLN 849.77 PLN	1197.33 PLN 1197.33 PLN
Nominal power	...	450 W
Apparent Power	...	750 VA
Rated voltage	5 V	...
Maximal voltage	6 V	...
Input voltage	...	165 ... 290 V AC
Voltage protection level line-line	$\leq 40 \text{ V} - 1 \text{ kV}/\mu\text{s}$...
Input frequency	...	45 ... 55 Hz
Voltage protection level line-PG	$\leq 600 \text{ V} - 1 \text{ kV}/\mu\text{s}$...
Output voltage	...	230 V AC (Pure Sine Wave)
Nominal discharge current (line-line)	20 A (10/1000 μs)	...
Output frequency	...	50 Hz
Nominal discharge current (line-PG)	20 A (10/1000 μs)	...
Voltage adjustment	...	$\pm 10 \%$
Frequency adjustment	...	—
Nominal power voltage	50 V	...
Transfer time	...	max. 4 ms
Maximal power voltage	56 V	...
Charging time (recover to 90% capacity)	...	8 hours
Nominal current	400 mA	...
Battery	...	2 x 6V/9Ah
Voltage protection level line-line for power	$\leq 95 \text{ V} - 1 \text{ kV}/\mu\text{s}$...
Voltage protection level line-PG for power	$\leq 1000 \text{ V} (1.2/50\mu\text{s})$...
Nominal discharge current line-line for power	10 A (10/1000 μs)	...
Nominal discharge current for power (line-PG)	2 kA (8/20 μs)	...
Estimated battery operation time	...	<ul style="list-style-type: none"> • 0.4 minutes @ 100% load • 8.7 minutes @ 50% load
Protection parameters compliance	Compliance with PN-EN61643-21	...
Number of channels	12	...
Number of outputs	...	4 pcs IEC320 C13 socket

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Sockets type	RJ45 (8P8C)	...
Management software	...	PowerMaster
Housing	Metal, black	...
Protections	...	<ul style="list-style-type: none"> • Fuse • Overvoltage • Overload protection • EPO (Emergency power off) switch
Operation state indication	...	<ul style="list-style-type: none"> • LCD display: operation mode, battery charging level, in/out voltage level • Sound signaling - with Mute function
Main features	...	<ul style="list-style-type: none"> • Auto restart while AC is recovering • "Cold Start" function • Expansion slot • Battery charge and maintenance control • USB/RS-232 communication port
Application	...	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type	...	RACK
Operation temp. / Relative humidity	...	0 °C ... 40 °C / 0 ... 90 % (non-condensing)
Weight	1.07 kg	8.81 kg
Dimensions	1 U Rack 19" 488 x 44 x 50 mm	435 x 235 x 44 mm ; RACK 19", 1U
Manufacturer / Brand	...	PowerWalker
Guarantee	2 years	2 years