



| | | |
|-------------------|--|---|
| | MOUNTING SCREWS SM-6/RACK-B | ACCESS POINT +ROUTER ARCHER-VR300 VDSL / ADSL 2.4 GHz, 5 GHz 300 Mbps + 867 Mbps TP- LINK |
| |  |  |
| | 2.00 PLN 2.00 PLN | 264.51 PLN 264.51 PLN |
| Application | Rack 19" / Rack 10" | ... |
| Frequency range | ... | 2.4 GHz, 5 GHz |
| Antenna type | ... | 4 x Omnidirectional antenna 5 dBi |
| Package includes | <ul style="list-style-type: none"> • 4 x M6 screw, Torx T-25 socket, • 4 x cage nut, • 4 x plastic shoulder washer, which protects the varnish coating of panels from damage during tightening the screws | ... |
| Material | Steel, Anodized surface | ... |
| Standards | ... | IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab ITU G.993.2, ITU-T G.993.5 (G.vector), ITU-T G.998.4 (G.INP), Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1 (G.hs), ITU-T G.995.1, ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis), ITU-T G.992.5 |
| LAN ports | ... | <ul style="list-style-type: none"> • 1 x 10/100 Mbps - LAN/WAN, • 3 x 10/100 Mbps - LAN |
| LED indicators | ... | Power, DSL, INTERNET, WLAN, LAN |
| WAN interface | ... | <ul style="list-style-type: none"> • 1 x RJ-11, ADSL / ADSL2 / ADSL2+ / VDSL / VDSL2 • 1 x RJ-45 |
| Transmitter power | ... | < 20 dBm @ 2.4 GHz , < 23 dBm @ 5 GHz |
| Baud rates | ... | 300 Mbps @ 2.4 GHz + 867 Mbps @ 5 GHz |
| DHCP server | ... | ✓ |

| | | |
|----------------------|-----|---|
| Firmware update | ... | ✓ |
| DDNS | ... | <ul style="list-style-type: none"> • DynDNS • No-IP |
| Operation modes | ... | ADSL/VDSL modem, Router, Access Point, Bridge WDS |
| Protections | ... | <ul style="list-style-type: none"> • LAN : NAT, SPI network firewall, Access control, IP-MAC Binding, Support DoS defence, parental control • WLAN : WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK, QSS (Quick Secure Setup) - WPS |
| Management interface | ... | Web browser, TP-LINK Tether |
| Main features | ... | <ul style="list-style-type: none"> • Enable/disable wireless network • SSID hiding • QoS • WMM (Wi-Fi Multimedia), • Rate limit • Internet access filtering • Wireless transmission statistics • Firewall • Remote management • DHCP : DHCP server, DHCP client list • Port forwarding : Virtual Server, Port Triggering, DMZ, ALG, UPnP • VPN networks: IPsec VPN, L2TP VPN, PPTP VPN, VPN Pass-through • IPv6 compliance • Static / dynamic routing • Port Mapping • IGMP Snooping V1/V2/V3 • Guest Network - a separate and secure network for guests • Built-in 4-port switch • ON/OFF button • WPS button • The WPS function allows to easy establish an encrypted connection • RESET button • The DSL line splitter included |
| Power supply | ... | 12 V DC / 1 A (power adapter included) |
| Operation temp | ... | 0 °C ... 40 °C |

| | | |
|-------------------------------|----------|-------------------|
| Permissible relative humidity | ... | 10 % ... 90 % |
| Weight | 0.035 kg | 0.31 kg |
| Dimensions | ... | 257 x 160 x 37 mm |
| Manufacturer / Brand | ... | TP-LINK |
| Guarantee | 2 years | 2 years |