


	SWITCHING ADAPTER PS-202F FOR TERRA SRM/SRO MULTISWITCHES F PLUG	NVR BCS-L-NVR6408-A-4K 64 CHANNELS + eSATA BCS Line	KEYSTONE CONNECTOR EX-F1C
			
	191.55 DKK 191.55 DKK	15816.15 DKK 15816.15 DKK	2.56 DKK 2.56 DKK
Adapter type	Switching
Standard	...	TCP/IP	...
Supported resolutions	...	max. 32 Mpx	...
Connector type	Adapter F socket / F socket
Power voltage	100 ... 240 V AC
Frequency range	50/60 Hz
Video outputs	...	2 pcs HDMI 4K 2 pcs VGA	...
Impedance	75 Ω
Output voltage	20 V DC
Maximal load	2 A
Audio support	...	64 Channels - Audio from cameras	...
Application	TERRA Multiswitches	...	Patch panel Keystone
Material	Metal / PET
Audio inputs	...	1 pcs CINCH	...
Output	F plug
Audio outputs	...	2 pcs CINCH	...
Main features	<ul style="list-style-type: none"> • Very easy and quick assembly • Corrosion resistance • Keystone assembly standard
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Bitrate	...	max. 384 Mbps	...
Supported hard drives	...	<ul style="list-style-type: none"> • 8 x 16 TB SATA + eSATA • Possibility of operation the disks in RAID 0/1/5/6/10 array 	...
Recording modes	...	Manual, Sensor, Motion detection, Schedule	...
External storage devices backup	...	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	...	<ul style="list-style-type: none"> • Records searching: by time and events type. Records playback: forward, backward, fast, slow • 1/4/9/16 channel synchronous playback 	...
Network interface	...	2 x RJ-45, 10/100/1000 Base-TX	...
Network functions	...	<ul style="list-style-type: none"> • Live image view, Playback the records, Backup the records, remote access, CMS application • Web-Server built-in 	...
Network protocols	...	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search, P2P, Auto Register	...
ONVIF	...	✓	...
Default IP address	...	192.168.1.108	...
Default admin user / password	...	admin / - The administrator password should be set at the first start	...
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager 	...
Web browser access ports	...	80, 37777	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

PC client access ports	...	37777	...
Mobile client access ports	...	37777	...
RTSP URL	...	<ul style="list-style-type: none"> rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream 	...
USB	...	<ul style="list-style-type: none"> • 2 pcs USB 2.0 • 2 pcs USB 3.0 	...
Serial ports	...	RS-485, RS-232	...
Alarm inputs / outputs	...	16 / 8	...
PTZ control	...	<ul style="list-style-type: none"> • IP Speed Dome Cameras • RS-485 	...
Motion Detection	...	✓	...
Intelligent image analysis	...	✓	...
Main features	...	<ul style="list-style-type: none"> • Intelligent image analysis : 10 rules - object detection (people, vehicle) • face detection • Face analysis: determination of sex, age and characteristic elements of appearance (glasses, facial hair, mask) • Face recognition • Support for up to 20 face databases, including 20 000 face images • SMD PLUS - searching for an object classified as: human, motor vehicle • Cooperation with POS (Point of Sale) terminals - POSNET <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none"> • ANPR • Authorized and unauthorized license plate lists: up to 20 000 records • counting people / vehicles • crowd gathering estimation • heat map • metadata handling - automatic photo taking and collection of information enabling the subsequent identification of people and vehicles that triggered the alarm (clothing, silhouette, face, features of motor and non-mechanical vehicles) 	...
Mouse support	...	✓	...
IR remote controller in the set	...	—	...
Power supply	...	100 ... 240 V AC	...
Power consumption	...	max. 13 W (without HDD)	...
Operation temp	...	-10 °C ... 55 °C	...
Weight	0.17 kg	6.3 kg	0.007 kg
Dimensions	...	440 x 454 x 95 mm	16 x 22 x 28 mm (W x H x D)
Supported languages	...	Polish, English	...
Manufacturer / Brand	...	BCS Line	...
Guarantee	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00