




	<a href="#">ROUTER RG-EW1800GXPRO</a> <a href="#">Wi-Fi 6, 2.4 GHz, 5 GHz</a> <a href="#">574 Mbps + 1201 Mbps</a> <a href="#">REYEE</a>	<a href="#">ACCESS POINT 4G LTE</a> <a href="#">+ROUTER TL-MR100</a> <a href="#">2.4 GHz 300 Mbps TP-LINK</a>
		
	535.80 PLN 535.80 PLN	258.75 PLN 258.75 PLN
Frequency range	2.4 GHz, 5 GHz	2.4 GHz
Antenna type	4 x Omnidirectional antenna - Integrated : • 6 dBi @ 5 GHz 2x2 MU-MIMO • 5 dBi @ 2.4 GHz 2x2 MU-MIMO	WiFi embedded , 2 x 4G LTE - 2 x SMA socket - Possibility to connect the wire antenna
Standards	IEEE 802.11 b/g/n @ 2.4 GHz , IEEE 802.11 a/n/ac/ax @ 5 GHz	IEEE 802.11 b/g/n
Baud rates	574 Mbps + 1201 Mbps	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 Mbps
LAN ports	4 x 10/100/1000 Mbps LAN 1 x 10/100/1000 Mbps Uplink	• 1 x 10/100 Mbps - LAN/WAN • 1 x 10/100 Mbps - LAN
Mobile phones support	Android: Free application <a href="#">Reyee Router</a> iOS (iPhone): Free application <a href="#">Reyee Router</a>	...
Receiver sensitivity	...	• 11g 54M : -74 dBm • 11n HT20 : -71 dBm • 11n HT40 : -68 dBm
Transmitter power	max. 20 dBm @ 2.4 GHz max. 27 dBm @ 5 GHz	< 20 dBm
Power consumption	≤ 18 W	...
LED indicators	Status, Mesh	Power, WAN, WLAN, LAN, GSM
Network type	...	• 4G : FDD-LTE B1/B3/B5/B7/B8/B20 - 2100 / 1800 / 850 / 2600 / 900 / 800 MHz • 4G : TDD-LTE B38/B40/B41 - 2600 / 2300 / 2500 MHz • 3G : HSPA/UMTS B1/B5/B8 - 2100 / 850 / 900 MHz

LTE	...	✓
QSS	...	—
WDS	...	—
DDNS	✓	<ul style="list-style-type: none"> <li>• DynDNS</li> <li>• No-IP</li> </ul>
DHCP server	✓	✓
Firmware update	✓	✓
Protections	WPA/WPA2 Support DoS defence	<ul style="list-style-type: none"> <li>• WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK</li> <li>• SPI network firewall</li> <li>• IP-MAC Binding</li> </ul>
Management interface	Web browser, Configuration using the Reyee Router application	Web browser
Operation modes	...	<ul style="list-style-type: none"> <li>• Router,</li> <li>• Router 4G LTE</li> </ul>
Main features	<ul style="list-style-type: none"> <li>• Support for Reyee Mesh technology,</li> <li>• MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network</li> <li>• Static / dynamic routing</li> <li>• Built-in 4-port switch</li> <li>• Access Point</li> <li>• QoS</li> <li>• Remote management</li> <li>• DMZ</li> <li>• UPnP</li> <li>• Port forwarding</li> <li>• parental control</li> <li>• Guest Network - a separate and secure network for guests</li> <li>• DHCP client list</li> <li>• SSID hiding</li> <li>• IPv6 compliance</li> <li>• PPTP VPN Server / Client</li> </ul>	<ul style="list-style-type: none"> <li>• Number of users - max. 32</li> <li>• SIM socket - The nanoSIM cards support</li> <li>• WPS/RESET button</li> <li>• Enable/disable wireless network</li> <li>• WMM (Wi-Fi Multimedia)</li> <li>• Wireless Network Schedule</li> <li>• Wireless transmission statistics</li> <li>• The failover function enabling automatic switching between 4G/WAN interface in the case of an Internet network connection loss</li> <li>• Static / dynamic routing</li> <li>• PPTP</li> <li>• L2TP</li> <li>• Remote management</li> <li>• DHCP client list</li> <li>• Port forwarding : UPnP, DMZ</li> <li>• Guest Network - a separate and secure network for guests</li> </ul>
Power supply	12 V DC / 1.5 A (power adapter included)	9 V DC / 0.85 A (power adapter included)
Operation temp	0 °C ... 45 °C	0 °C ... 40 °C
Permissible relative humidity	5 % ... 95 % (non-condensing)	10 % ... 90 % (non-condensing)
Weight	0.54 kg	0.184 kg

Dimensions	203 x 180 x 178 mm	155 x 114 x 34 mm
Manufacturer / Brand	RUIJIE / REYEE	TP-LINK
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00