



	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-B-EA15FSR4(2.0) - 5 Mpx 2.8 mm BCS BASIC	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-EA15FR3-G(H2) - 5 Mpx 3.6 mm
		
	130.00 PLN 130.00 PLN	145.00 PLN 145.00 PLN
Standard	AHD / HD-CVI / HD-TVI / CVBS	AHD / HD-CVI / HD-TVI / PAL
Resolution	<ul style="list-style-type: none"> • 2880 x 1620 - 5 Mpx @ HD-CVI @ 25 fps • 2880 x 1620 - 5 Mpx @ AHD @ 20 fps • 2880 x 1620 - 5 Mpx @ HD-TVI @ 20 fps / 12.5 fps • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 30 fps / 25 fps • 1920 x 1080 - 2 Mpx @ AHD / HD-CVI / HD-TVI @ 30 fps / 25 fps • 960 x 576 - 960H @ PAL / NTSC 	2704 x 1950 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p
Sensor	1/2.7 " Progressive Scan CMOS	1/2.5 " Progressive Scan CMOS
Lens	2.8 mm	3.6 mm, F1.2
View angle	• 109 °	• 100 °
Range of IR illumination	40 m	30 m
IR illuminator power adjustment	Automatic	Automatic
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
OSD menu	OSD menu available via recorder	OSD menu available via BCS-XVR recorder
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC - configurable Back Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Mirror - Mirror image 	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • BLC - Back Light Compensation • 3D-DNR - Digital Noise Reduction • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance
Power supply	12 V DC / 283 mA	12 V DC / 420 mA

Power consumption	< 3.4 W	< 5 W
Housing	Dome, Metal	Dome, Metal
Color	White	Graphite
"Index of Protection"	IP67	IP66
Mechanical protection class	—	—
Operation temp	-20 °C ... 60 °C	-20 °C ... 60 °C
Weight	0.33 kg	0.3 kg
Dimensions	Ø 111 x 98 mm	Ø 80 x 94 mm
Manufacturer / Brand	BCS BASIC	BCS
Guarantee	3 years	3 years