



	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1801T-Z-A-27135-S2 - 8.3 Mpx 2.7 ... 13.5 mm - MOTOZOOM DAHUA	AC POWER SUPPLY ADAPTER TR-40VA/NORATEL SATEL
		
	849.00 PLN 849.00 PLN	114.58 PLN 114.58 PLN
Adapter type	...	Transforming
Power voltage	...	230 ... 250 V AC
Standard	AHD, HD-CVI, HD-TVI, CVBS	...
Frequency range	...	47 ... 63 Hz
Sensor	Progressive Scan CMOS	...
Matrix size	8.3 Mpx	...
Output voltage	...	16 V, 18 V AC
Maximal load	...	2.22 A
EN norm	...	EN61558-2-6
Test voltage between PRI/SEC	...	AC 4kV RMS
Safety class	...	II
Isolation class	...	B (130°C)
Output power	...	40 VA
Application	...	<ul style="list-style-type: none"> • to alarm systems powering • to automatic systems • to low-voltage light installation powering
Output	...	2 pcs
Resolution	<ul style="list-style-type: none"> • AHD / HD-CVI / HD-TVI : 3840 x 2160 - 8.3 Mpx, 4K UHD • HD-CVI : 2880 x 1620 - 5 Mpx 2560 x 1440 - 3.7 Mpx • CVBS : 960 x 576 - 960H 	...
Lens	2.7 ... 13.5 mm - Motozoom, AutoFocus	...
View angle	<ul style="list-style-type: none"> • 114 ° ... 32 ° (manufacturer data) • 110 ° ... 31 ° (our tests result) 	...
Range of IR illumination	60 m	...
IR illuminator power adjustment	Automatic	...

Video output	AHD / HD-CVI / HD-TVI / CVBS - 1 Vpp / 75 Ω	...
Audio	Microphone built-in - HD-CVI only	...
Main features	<ul style="list-style-type: none"> • Motozoom lens, AutoFocus - The control possible only from Dahua recorders in HD-CVI mode • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • D-ZOOM - Digital Zoom • Mirror - Mirror image • Privacy zones - max. 8 • Sharpness - sharper image outlines 	...
OSD menu	OSD menu available via DAHUA recorder	...
Power supply	12 V DC / 660 mA	...
Power consumption	≤ 7.9 W	...
Housing	Dome, Metal	...
Color	White	...
"Index of Protection"	IP67	IP44
Vandal-proof	—	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.59 kg	1.01 kg
Dimensions	Ø 122 x 105 mm	124 x 72 x 67 mm
Manufacturer / Brand	DAHUA	SATEL
Guarantee	3 years	2 years