



	IP CAMERA IPC3624LE-ADF28K-WL ColorHunter - 4 Mpx 2.8 mm UNIVIEW	SET OF UTP / 2-WIRE CONVERTERS FOR LAN+POE TRANSMISSION ETH10-2WIRE-SET 2 PCS SET ATTE
		
	891.65 PLN 891.65 PLN	369.00 PLN 369.00 PLN
Standard	TCP/IP	...
Sensor	1/1.8 " Progressive Scan CMOS	...
Matrix size	4 Mpx	...
Connectors	...	<ul style="list-style-type: none"> • 1 pcs RJ45 • 1 pcs terminals (screw terminals) - 0.32 ... 3.3 mm² (22 ... 12 AWG)
LAN ports	...	1 pcs RJ45 10 Mbps
Resolution	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p	...
Lens	2.8 mm @ F1.0	...
View angle	<ul style="list-style-type: none"> • 110 ° (manufacturer data) • 110 ° (our tests result) 	...
White light LED illuminator range	30 m	...
S/N ratio	> 52 dB	...
RS-485 interface	—	...
Memory card slot	Micro SD memory cards up to 128GB support (possible local recording)	...
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network • Audio detection 	...

Connectors description	...	<p>ETH10-2WIRE-TX :</p> <ul style="list-style-type: none"> • PoE IN - Passive PoE ≤ 30 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W ("+" : 1, 2 pins; "+/-" : 3, 6 pins) or ("+" : 4, 5 pins; "+/-" : 7, 8 pins) • Power • DATA - 2-wire <p>ETH10-2WIRE-RX :</p> <ul style="list-style-type: none"> • PoE OUT - Passive PoE ("+" : 4, 5 pins; "-" : 7, 8 pins) • Power • DATA - 2-wire
Transmission speed	...	10 Mbps
Main stream frame rate	25 fps @ 4 Mpx	...
Network interface	10/100 Base-TX (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	32	...
ONVIF	✓	...
Mobile phones support	<p>Access by a cloud (P2P)</p> <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView 	...
Transmission range	...	<ul style="list-style-type: none"> • 1000 m @ 2-wire • 100 m @ UTP : Switch PoE - ETH10-2WIRE-TX • 100 m @ UTP : ETH10-2WIRE-RX - IP Camera
Default IP address	DHCP or 192.168.1.13	...
Default admin user / password	admin / 123456	...
LED indicators	...	<ul style="list-style-type: none"> • Power • LAN • 2-wire
Web browser access ports	80, 554	...
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	...
Mobile client access ports	80	...
Port ONVIF	80	...
RTSP URL	<p>rtsp://192.168.1.13:554/unicast/c1/s0/live</p> <p>- Main stream</p> <p>rtsp://192.168.1.13:554/unicast/c1/s1/live</p> <p>- Sub stream</p>	...

Protections	...	<ul style="list-style-type: none"> • Overvoltage - LAN, DATA • Protection against reverse polarity connection - Power • Overload 0.6 A - PoE IN ETH10-2WIRE-TX
Main features	...	<ul style="list-style-type: none"> • Plug & Play • Support for IP cameras and network devices • Full transparency for networks • Operation modes - Set with jumpers
Main features	<ul style="list-style-type: none"> • ColorHunter - colorful night mode • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • Auto White Balance • Day/Night mode (color/b&w/auto) • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • Possibility to change the resolution, quality and bit rate • Sharpness - sharper image outlines • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Intelligent image analysis : crossing the line (tripwire), intrusion (human silhouette) • Overvoltage protection : 4 kV 	...
Operation temp	...	-25 °C ... 65 °C
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 500 mA 	ETH10-2WIRE-TX : <ul style="list-style-type: none"> • 30 ... 56 V DC - PoE • 10 ... 56 V DC - Power ETH10-2WIRE-RX : <ul style="list-style-type: none"> • 10 ... 56 V - Power • The output PoE voltage is equal to the input voltage

Power consumption	≤ 5.9 W	1.35 W (total)
Housing	Dome, Metal + Plastic	Plastic (PC)
Color	White	...
"Index of Protection"	IP67	IP20
Vandal-proof	—	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.46 kg	0.03 kg (single element)
Dimensions	Ø 118 x 106 mm	51 x 51 x 24 mm (single element)
Supported languages	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian	...
Manufacturer / Brand	UNIVIEW	ATTE
Guarantee	3 years	3 years