

	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR DS-7204HUHI-K1/E(C)(S) 4 CHANNELS Hikvision	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1200TL-A-0360B-S5 - 1080p 3.6 mm DAHUA	65 dB	...
OSD menu	...	✓	...	
Power consumption	...	≤ 5.3 W	• 14.5 W (typical) • 0.5 W (in standby mode)	
Housing	...	Compact, Plastic / Metal	...	
"Index of Protection"	...	IP67	...	
Operation temp	...	-40 °C ... 60 °C	...	
Image records resolutions	<ul style="list-style-type: none"> • HD-TVI : 8.3 Mpx 4K UHD - 3840 x 2160 1 CH only , 8M-N - 1920 x 2160 , 5 Mpx - 2560 x 1944 , 3.7 Mpx - 2560 x 1440 , 3 Mpx - 1920 x 1536 , 1080p - 1920 x 1080 , 720p - 1280 x 720 , • AHD / HD-CVI : 5 Mpx - 2560 x 1944 , 3.7 Mpx - 2560 x 1440 , 1080p - 1920 x 1080 , 720p - 1280 x 720 , • PAL : 960H - 960 x 576 , • IP : max. 8 Mpx - 3840 x 2160 	
Recording speed adjustment	<ul style="list-style-type: none"> 8 Mpx IP @ 1 ... 25 fps 8 Mpx @ 1 ... 8 fps 8M-N @ 1 ... 12 fps 5 Mpx @ 1 ... 12 fps 4 Mpx @ 1 ... 15 fps 3 Mpx @ 1 ... 18 fps 1080p @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel 	
Operation modes	4 x HD-TVI / AHD / HD-CVI / CVBS / IP + 4 x IP	
Recording modes	Manual, Motion Detection, Schedule	
Supported hard drives	1 x 10 TB SATA	
External storage devices backup	Backup to USB drive (pendrive, external drive)	
Searching and playback the records	Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 4 cameras in the same time	
Network interface	1 x RJ-45 - 10/100 Base-TX	
Bitrate	32 ... 10240 kbps	
Network functions	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters	
Network protocols	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF	

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile phones support	Port no.: 8000 or access by a cloud (P2P) Android: Free application iVMS-4500 or Hik-Connect iOS (iPhone): Free application iVMS-4500 or Hik-Connect
Default IP address	DHCP or 192.168.1.64
Default admin user / password	admin / - The administrator password should be set at the first start
Web browser access ports	80
PC client access ports	554 RTSP, 8000
Mobile client access ports	8000
Port ONVIF	80
RTSP URL	<ul style="list-style-type: none"> • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
Alarm inputs / outputs	—
PTZ control	Control compatible with coax HD-TVI Hikvision
Motion Detection	Split the screen into zones : 22 x 18 motion zones
USB	2 x USB 2.0
Mouse support	✓
IR remote controller in the set	—
Main features	Intelligent image analysis : crossing the line (tripwire), intrusion, scene changing	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Sharpness - sharper image outlines • AGC - Automatic Gain Control • Privacy zones • Mirror - Mirror image • Auto White Balance 	...
Power supply	12 V DC / 1.5 A (power adapter included)	12 V DC / 440 mA	230 V AC
Color	Black	White	...
Weight	0.89 kg	0.28 kg	2.16 kg
Dimensions	260 x 236 x 48 mm	80 x 75 x 199 mm	<ul style="list-style-type: none"> • 465 x 345 x 170 mm (with stand) • 465 x 285 x 48 (without stand)
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand	Hikvision	DAHUA	PHILIPS
SAP Code	300227087



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Guarantee	3 years	3 years	2 years
-----------	---------	---------	---------



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00