

	ENCLOSURE ME-10 ROGER	IP CAMERA IPC-HDW1439V-A-IL-BLACK Smart Dual Light - 3.7 Mpx 2.8 mm DAHUA
		
	290.00 PLN 290.00 PLN	660.00 PLN 660.00 PLN
Housing type	Surface-mounted	...
Standard	...	IP
Tamper contact	Tamper detection - removing from mounting surface ; 30 V DC / 0.5 A	...
Material	Stainless sheet - powder painting	...
Resolution	...	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Sensor	...	1/2.9 " Progressive Scan CMOS
Lens	...	2.8 mm
View angle	...	94 °
White light LED illuminator range	...	30 m
Range of IR illumination	...	30 m
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Main stream frame rate	...	25 fps @ 3,7 Mpx
Memory card slot	...	—
Alarm inputs / outputs	...	—
Audio	...	<ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network • Compliance with the AAC standard • Audio detection
Interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	6
ONVIF	...	✓
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address	...	192.168.1.108
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 37777
PC client access ports	...	37777

Mobile client access ports	...	37777
Port ONVIF	...	80
RTSP URL	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Image rotation and mirror • Motion Detection - max. 4 configurable zones • Privacy zones - max. 4 • Intelligent image analysis : Human detection
Housing	...	Dome - Metal + Plastic
Color	Gray	Black
"Index of Protection"	...	IP67
Mechanical protection class	...	—
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 380 mA
Power consumption	...	<ul style="list-style-type: none"> • ≤ 5.7 W @ PoE • ≤ 4.6 W @ 12 V DC
Operation temp	...	-40 °C ... 60 °C
Weight	0.32 kg	0.33 kg
Dimensions	184 x 85 x 76 mm	Ø 110 x 101 mm
Supported languages	...	English, Spanish, Russian
Manufacturer / Brand	ROGER	DAHUA
Guarantee	3 years	3 years

