



	IP CAMERA IPC3614SB-ADF28KMC-I0 Tri-Guard - 4 Mpx 2.8 mm UNIVIEW	IP CAMERA IPC3614LB-SF28-A - 3.7 Mpx 2.8 mm UNIVIEW
		
	1134.54 PLN 1134.54 PLN	462.11 PLN 462.11 PLN
Standard	TCP/IP	TCP/IP
Sensor	1/2.7 " Progressive Scan CMOS	1/3 " Progressive Scan CMOS
Matrix size	4 Mpx	4 Mpx
Scanning system	...	Progressive
Resolution	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	2.8 mm	2.8 mm
View angle	• 101 ° (manufacturer data) • 96 ° (our tests result)	• 97 ° (manufacturer data) • 90 ° (our tests result)
White light LED illuminator range	30 m	...
Range of IR illumination	30 m	30 m
S/N ratio	> 56 dB	> 52 dB
RS-485 interface	—	—
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	—
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG	Ultra 265 / H.265 / H.264
Alarm inputs / outputs	—	—
Audio	• Microphone built-in, • Speaker built-in • Audio transmission via network • Audio detection	—
Main stream frame rate	25 fps @ 4 Mpx	25 fps @ 3.7 Mpx
Network interface	10/100 Base-TX (RJ-45)	10/100 Base-T (RJ-45)
Network protocols	...	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL / TLS
WEB Server	Built-in	Built-in
Max. number of on-line users	32	32
ONVIF	✓	✓
Mobile phones support	Access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView	Access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address	DHCP or 192.168.1.13	DHCP or 192.168.1.13

Default admin user / password	admin / 123456	admin / 123456
Web browser access ports	80, 554	80, 554
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	80	80
Port ONVIF	80	80
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • Active deterrence function - Light and sound alarm • F-DNR (Defog) - Reduction of image noise caused by precipitation • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Auto White Balance • ROI - improve the quality of selected parts of image • Possibility to change the resolution, quality and bit rate • Sharpness - sharper image outlines • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Intelligent image analysis : crossing the line (tripwire), intrusion, entering the marked area, leaving the marked area, people counting, crowd gathering estimation, face detection • Overvoltage protection : 4 kV 	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Privacy zones - max. 4 • Motion Detection - max. 4 zones • Sharpness - sharper image outlines
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 625 mA 	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 410 mA
Power consumption	≤ 7.5 W	≤ 5 W
Housing	Dome, Metal	Dome, Metal + Plastic
Color	White	White
"Index of Protection"	IP67	IP67
Vandal-proof	—	—

Operation temp	-30 °C ... 60 °C	-30 °C ... 60 °C
Weight	0.42 kg	0.28 kg
Dimensions	Ø 110 x 95 mm	Ø 118 x 97 mm
Supported languages	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovenian, Hungarian, Italian
Manufacturer / Brand	UNIVIEW	UNIVIEW
Guarantee	3 years	3 years