



	<a href="#">ROUTER RG-EG310GH-E REYEE</a>	<a href="#">SWITCH POE TL-SF1008P 8-PORT TP-LINK</a>
		
	1298.00 PLN 1298.00 PLN	230.10 PLN 230.10 PLN
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z	...
LAN ports	<ul style="list-style-type: none"> <li>• 6 x LAN 10/100/1000 Mbps (RJ-45)</li> <li>• 3 x LAN/WAN 10/100/1000 Mbps (RJ-45)</li> </ul>	8 x RJ45 ( 4 PoE )
WAN interface	<ul style="list-style-type: none"> <li>• 1 x WAN x 10/100/1000 Mbps (RJ-45)</li> </ul>	...
Management	...	—
LED indicators	Status, Link/Act	...
DDNS	✓	...
LED diodes	...	Power, Link/Act, PoE
DHCP server	✓	...
Port USB	—	...
Firmware update	✓	...
Power supply PoE	—	...
Transmission speed	...	<ul style="list-style-type: none"> <li>• Ethernet - 10 Mbps Half Duplex, 20 Mbps Full Duplex</li> <li>• Fast Ethernet - 100 Mbps Half Duplex, 200 Mbps Full Duplex</li> </ul>
Maximal output power	...	15.4 W / port PoE
Maximal total power	...	53 W
MAC addresses table	...	1k
Protections	<ul style="list-style-type: none"> <li>• ACL</li> <li>• IP-MAC Binding</li> <li>• MAC addresses filtering</li> <li>• Support for dynamic ARP mapping and static table</li> <li>• NAT / NAPT</li> <li>• Port Mapping</li> <li>• Mechanisms to prevent the most common types of DoS (Denial-of-Service) attacks</li> </ul>	...
Certificates	...	FCC Class B, CE
Management interface	<ul style="list-style-type: none"> <li>• Ruijie Cloud Central Management System</li> <li>• Configuration using the Ruijie Reeye application</li> <li>• Remote management</li> <li>• Web browser</li> </ul>	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile phones support	Android: Free application <a href="#">Ruijie Reyee</a> iOS (iPhone): Free application <a href="#">Ruijie Reyee</a>	...
Main features	<ul style="list-style-type: none"> <li>• VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc.</li> <li>• Static / dynamic routing</li> <li>• WAN : PPPoE, PPTP, L2TP</li> <li>• DHCP client/server support</li> <li>• Access Control List - ACL package filtering based on source and destination IP addresses</li> <li>• Rate limit</li> <li>• Load balance</li> <li>• NAT</li> <li>• Reboot schedule</li> <li>• View topology and network status</li> <li>• RESET button</li> </ul>	...
Power supply	100 ... 240 V AC, 50 / 60 Hz	48 V DC / 1.25 A (power adapter included)
Power consumption	≤ 15 W	...
Operation temp	0 °C ... 40 °C	...
Permissible relative humidity	10 % ... 90 % (non-condensing)	...
Weight	2.4 kg	0.8 kg
Dimensions	440 x 207 x 44 mm	171 x 98 x 27 mm
Manufacturer / Brand	RUIJIE / REYEE	TP-LINK
Guarantee	2 years	3 years