




	<a href="#">SMART PROXIMITY SWITCH PROXISWITCH-V2/BLEBOX 12 ... 24 V DC</a>	<a href="#">MODULAR PLUG RJ45/C53*P100</a>	<a href="#">CABLES TESTER CS-NT24-PRO</a>
			
	56.10 PLN 56.10 PLN	17.58 PLN 17.58 PLN	841.60 PLN 841.60 PLN
Application	Non-contact switching on and off	...	...
Rated voltage	12 ... 24 V DC	...	...
Maximal total load	120 W	...	...
In package	...	<b>100 pcs The price for package</b>	...
Total maximal current	5 A	...	...
Tested cables	...	...	STP / UTP cat. 5, 5e, 6, 6e - RJ45 (8P8C), RJ11 (6P4C), Coaxial cable
Number of inputs	0	...	...
Number of outputs	1	...	...
Connector type	screw terminals	...	...
Connector type	...	RJ 45 - Plug 8 pin	...
Wireless	—	...	...
Attachment of connector elements	...	Crimping	...
Mobile phones support	—	...	...
Wire mounting	...	Clamping on each wire with 3-pin edge	...
Application	...	Twisted-pair cable	...
Material	...	• PET	...
Example of application	...	UTP cat. 5, 5e	...
Power supply	...	...	Cables tester : Li-Ion battery 3.7 V / 2000 mAh, USB DC 5V/2A power adapter (included) Probe : 2 x 1.5V, type AA/LR6/FR6 battery (not included)
Typical battery charge time	...	...	3 h
Backup time	...	...	16 h
Housing	Plastic	...	...
"Index of Protection"	IP20	...	...
Color	Black	...	...
Operation temp	-20 °C ... 50 °C	...	...
Manufacturer / Brand	BleBox	...	...

Main features	<ul style="list-style-type: none"> <li>• Operation modes : bistable, bistable + state memory, monostable NO, monostable NC,</li> <li>• Detection range : 3 cm</li> <li>• Trigger time : max. 8 s</li> <li>• Possibility to hide the sensor</li> <li>• Automatic calibration</li> <li>• LED indication</li> </ul>	<ul style="list-style-type: none"> <li>• Very easy and quick assembly</li> <li>• To crimp use the crimping tool HT-546</li> </ul>	<ul style="list-style-type: none"> <li>• 2.4 " LCD display - 320 x 240 px</li> <li>• Cable test and cable tracer : cable type, UTP cable's sequence and type test, the fault of RJ45 connector</li> <li>• Test TDR - RJ45 : pair status, length, attenuation, reflectivity, impedance, skew - Length of the cable max. 180 m</li> <li>• Test TDR 2.0 : Searching for a wire fault point - Length of the cable max. 1200 m,</li> <li>• Detection of the connected port in switch</li> <li>• Test PING : correct operation of the IP camera's Ethernet port, correct IP address</li> <li>• IP Scan</li> <li>• Identification of the network port and duplex mode</li> <li>• Identification the wire in the group of wires</li> <li>• Telephone line condition detection</li> <li>• Detecting and locating a cable break or short circuit</li> <li>• HD coaxial video level meter</li> <li>• Automatic power-off : 10 ... 120 minutes</li> </ul>
Weight	0.018 kg	0.001 kg	0.34 kg - Cables tester 0.11 kg - Probe
Dimensions	39 x 39 x 16 mm	...	175 x 88 x 40 mm - Cables tester 220 x 47 x 32 mm - Probe
Guarantee	2 years	5 years	2 years