



	<a href="#">ACCESS CONTROLLER MC16-PAC-EX-1-KIT ROGER</a>	<a href="#">SWITCH POE IP-5-11-M2 5-PORT ATTE</a>
		
	1825.00 PLN 1825.00 PLN	475.00 PLN 475.00 PLN
Number of served transitions	1 (two-way)	...
Support	RACS 5 v2 (Roger)	...
Number of supported readers	4 pcs	...
Battery backup support	max. 7 Ah	...
Input lines	8 pcs	...
Output lines	8 pcs	...
LAN ports	...	<ul style="list-style-type: none"> <li>• 1 x RJ45 10/100 Base-T - Uplink</li> <li>• 5 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE</li> </ul>
Management	...	—
Communication	<ul style="list-style-type: none"> <li>• RS-485,</li> <li>• RACS 5 v2 (Roger),</li> <li>• Wiegand</li> </ul>	...
LED diodes	...	Power, LAN
Transmission speed	...	10 / 100 Mbps : 1 Port LAN + 5 LAN & PoE ports
Maximal output power	...	<ul style="list-style-type: none"> <li>• 40 W @ Passive PoE - 1 ... 4 ports,</li> <li>• 70 W @ Passive PoE - Port 5,</li> <li>• 30 W @ PoE (802.3af/at) - 1 ... 5 ports</li> </ul>
Maximal total power	...	96 W
Operation modes	...	<ul style="list-style-type: none"> <li>• Normal : 100 m @ 10/100 Mb/s - 1 ... 5 ports</li> <li>• Long Range : 280 m @ 10 Mb/s - 1 ... 4 ports ; 100 m @ 10/100 Mb/s - Port 5</li> <li>• Port LAN 6 - Uplink</li> </ul>
Operation temp	5 °C ... 40 °C	...
Permissible relative humidity	10 % ... 95 % (non-condensing)	...

Main features	<ul style="list-style-type: none"> <li>• Metal housing</li> <li>• Power output : 1 x 0.2 A, 1 x 1.0 A</li> <li>• Power adapter : 24 V DC / 2.2 A,</li> <li>• Battery charging current : 0.3 A</li> <li>• Protection against deep discharge of the battery</li> <li>• Tamper detection - opening the enclosure</li> <li>• Place for battery - 12 V / 7 Ah</li> <li>• Integrated support in VISO EX software</li> <li>• Functions in the VISO EX system: - MSSQL database</li> <li>- work in distributed systems</li> <li>- multi-station work</li> <li>- monitoring of transitions with video preview</li> <li>- T&amp;A event reporting</li> <li>- maximum number of transitions in the system - unlimited</li> <li>- division of the system into partitions operated by independent operators</li> <li>- tool for integration with RACS5 (API) systems</li> <li>- integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems)</li> </ul>	<ul style="list-style-type: none"> <li>• Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port)</li> <li>• The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports</li> <li>• The modular design streamlines service tasks and enables quick and easy system expansion</li> <li>• The raster system of module assembly facilitates the expansion of the device by further modules</li> <li>• The ABOX-M2 mounting enclosure is equipped with 7 cable entries with glands in the 6 x M16 + 1 x M20 arrangement</li> </ul>
Power supply	230 V AC	230 V AC - cable terminals
Weight	3.88 kg	0.65 kg
Dimensions	405 x 365 x 120 mm	226 x 148 x 80 mm
Manufacturer / Brand	ROGER	ATTE
Guarantee	3 years	3 years