

|                             | <a href="#">STYROFOAM PLUG<br/>FISCHER FID-50</a>                                 | <a href="#">CUSTOMER PREMISES<br/>EQUIPMENT PFWB5-90AC<br/>DAHUA</a>                                        |
|-----------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|
|                             |  |                          |
|                             | 3.38 PLN<br>3.38 PLN                                                              | 1846.00 PLN<br>1846.00 PLN                                                                                  |
| Length                      | 50 mm                                                                             | ...                                                                                                         |
| Diameter                    | Ø 25 mm                                                                           | ...                                                                                                         |
| Frequency range             | ...                                                                               | 5150 MHz ... 5850 MHz                                                                                       |
| Thickness of the Styrofoam  | ≥ 50 mm                                                                           | ...                                                                                                         |
| Diameter of the screw       | Ø 4.5 mm / Ø 5 mm                                                                 | ...                                                                                                         |
| Antenna type                | ...                                                                               | 18 dBi, 2x2 MIMO -<br>Bandwidth 5 GHz                                                                       |
| Standards                   | ...                                                                               | IEEE 802.11 a/n/ac                                                                                          |
| Baud rates                  | ...                                                                               | max. 866 Mbps                                                                                               |
| LAN ports                   | ...                                                                               | 1 x 10/100/1000 Mbps                                                                                        |
| Vertical beam width (V)     | ...                                                                               | 20 °                                                                                                        |
| Horizontal beam width (H)   | ...                                                                               | 90 °                                                                                                        |
| Operation modes             | ...                                                                               | WDS client, TDMA client,<br>WDS Base Station, TDMA<br>Base Station, ARP NAT Base<br>Station, Bridge, Router |
| Protections                 | ...                                                                               | Overvoltage protection                                                                                      |
| Transmitter power           | ...                                                                               | 30 dBm                                                                                                      |
| Wireless transmission range | ...                                                                               | <ul style="list-style-type: none"> <li>Recommended ≤ 5 km</li> <li>max. 7 km</li> </ul>                     |
| Memory                      | ...                                                                               | 64 MB RAM, 16 MB Flash                                                                                      |
| Processor                   | ...                                                                               | QCA9563 750 MHz                                                                                             |
| Power supply PoE            | ...                                                                               | ✓                                                                                                           |
| Power supply                | ...                                                                               | 12 V ... 24 V DC - Passive<br>PoE (power adapter<br>included)                                               |
| Power consumption           | ...                                                                               | 10 W                                                                                                        |
| Operation temp              | ...                                                                               | -30 °C ... 70 °C                                                                                            |
| Weight                      | 0.004 kg                                                                          | 0.57 kg                                                                                                     |
| Dimensions                  | ...                                                                               | 383 x 100 x 98 mm                                                                                           |
| Manufacturer / Brand        | ...                                                                               | DAHUA                                                                                                       |
| Guarantee                   | 2 years                                                                           | 3 years                                                                                                     |