




	<a href="#">ACCESS CONTROLLER WITH FACE RECOGNITION ASI6213J-MW - 1080p DAHUA</a>	<a href="#">SET OF UTP / COAXIAL CONVERTERS FOR LAN+POE TRANSMISSION XCOAX4-SET 2 PCS SET ATTE</a>	<a href="#">EXTENDER EXT-POE2H IN A HERMETIC CASING PULSAR</a>
			
	2544.00 PLN 2544.00 PLN	469.00 PLN 469.00 PLN	279.00 PLN 279.00 PLN
Sensor	CMOS	...	...
Matrix size	2.1 Mpx	...	...
Standards	...	...	PoE : IEEE 802.3at, IEEE 802.3af
Connectors	...	<ul style="list-style-type: none"> <li>• 1 pcs RJ45</li> <li>• 1 pcs cable terminal</li> <li>• 1 pcs BNC</li> </ul>	...
Input voltage	...	...	42 ... 57 V DC
Output voltage	...	...	42 ... 57 V DC
LAN ports	...	1 pcs RJ45 100 Mbps	...
Number of inputs	...	...	1
Resolution	1920 x 1080 - 1080p	...	...
Number of outputs	...	...	2
Connector	...	...	3 x RJ-45 socket
Standard	TCP/IP	...	...
IR illuminator	✓	...	...
LED illuminator	✓	...	...
Temperature measurement	—	...	...
Supported data rates	...	...	<ul style="list-style-type: none"> <li>• Range : 100 m - Input, 100 m - 2 x Output,</li> <li>• Supported data rates 10 / 100 Mbps - Fast Ethernet</li> </ul>
Temperature measurement range	—	...	...
Accuracy of temperature measurement	—	...	...
Output power	...	...	15.4 W / Port PoE OUT 1/2 , max. 20 W (total)
Face recognition distance	0.3 m ... 1.5 m (max 6000 faces in the database)	...	...
RFID proximity reader built-in	<ul style="list-style-type: none"> <li>• 13.56 MHz S50</li> <li>• Memory of 6000 RFID cards</li> </ul>	...	...
Internal memory	Support storage of 150 000 records	...	...
Video output	—	...	...

RS-485 interface	✓	...	...
LAN+PoE port configuration description	...	<ul style="list-style-type: none"> <li>• xCOAX4-SW : PoE IN - Passive PoE ≤ 30 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W ("+"-": 1, 2 pins; "+"-": 3, 6 pins) or ("+"-": 4, 5 pins; "+"-": 7, 8 pins)</li> <li>• xCOAX4-CAM : Port LAN 10/100Mb or LAN + PoE OUT - PoE (802.3bt) ≤ 60 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W</li> </ul>	...
RS-232 interface	—	...	...
Wiegand interface	✓	...	...
Operation temp. / Relative humidity	...	...	-10 ... 40 °C / 10 ... 90 %
USB	1 x USB 2.0	...	...
Memory card slot	—	...	...
Alarm inputs / outputs	1 / 1 - Relay outputs	...	...
Audio	Voice message	...	...
Transmission range	...	<ul style="list-style-type: none"> <li>&lt; 1000 m @ Coaxial cable</li> <li>&lt; 100 m @ xCOAX4-SW - Switch PoE</li> <li>&lt; 100 m @ xCOAX4-CAM - IP Camera</li> </ul>	...
Network interface	1 x 10/100 Base-T (RJ-45)	...	...
LED indicators	...	<ul style="list-style-type: none"> <li>• PoE</li> <li>• LAN</li> <li>• Link</li> <li>• 10Mb</li> </ul>	LAN, PoE
Protections	...	<ul style="list-style-type: none"> <li>• Overvoltage - LAN, BNC</li> <li>• Short-circuit - xCOAX4-SW</li> </ul>	<ul style="list-style-type: none"> <li>• Overvoltage</li> <li>• Overload</li> <li>• Short-circuit</li> </ul>
Network protocols	IPv4, RTSP, RTP, TCP, UDP, P2P	...	...
WEB Server	Built-in	...	...
ONVIF	—	...	...
Default IP address	192.168.1.108	...	...
Main features	...	<ul style="list-style-type: none"> <li>• Plug &amp; Play</li> <li>• Support for IP cameras and network devices</li> <li>• Full transparency for networks</li> <li>• Watchdog function - Coaxial cable</li> </ul>	...

Default admin user / password	admin / - The administrator password should be set at the first start	...	...
Web browser access ports	80, 37777	...	...
PC client access ports	37777	...	...
Operation temp	...	-25 °C ... 65 °C	...
Main features	<ul style="list-style-type: none"> <li>• Built-in LCD display showing the image from the video camera - 4.3 " capacitive touch screen, 480 x 272 px</li> <li>• Identification modes : PIN, Proximity identifier 13.56 MHz S50, Face recognition, Any combination of the above</li> <li>• 6000 users</li> <li>• Software update via network</li> <li>• Real-time Surveillance</li> <li>• Multiple Authentication</li> <li>• Take face image after swiping card</li> <li>• Auto-Registration</li> <li>• Backup to USB drive (pendrive, external drive)</li> <li>• Output button support</li> <li>• Door status detection</li> <li>• Lock control</li> <li>• Function to prevent of multiple use of the same code/card to gain access (anti-passback)</li> <li>• Auto-uploads alarm messages to Master or client station after entering the duress code to open the door</li> <li>• Ability to work with reed switch and signalling the door being opened too long</li> <li>• 128 General Purpose Schedules</li> <li>• Unlocking the transition only when more than one user is present</li> <li>• Tamper protections</li> </ul>	...	...



Power supply	12 V DC / 2 A (power adapter included)	xCOAX4-SW : • 10 ... 58 V DC - cable terminal • PoE 802.3af/at / PASSIVE • The output PoE voltage is equal to the input voltage	...
Power consumption	≤ 24 W	1.35 W (total)	...
Housing	Metal + Tempered glass	Plastic (PC)	Plastic, hermetic
Color	Black + Silver	...	...
"Index of Protection"	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP20	IP56
Operation temp	-30 °C ... 60 °C	...	...
Weight	0.43 kg	0.033 kg (single element)	0.55 kg
Dimensions	174 x 88 x 23 mm	• 73 x 52 x 20 mm - xCOAX4-SW • 73 x 52 x 20 mm - xCOAX4-CAM	198 x 148 x 78 mm
Supported languages	English	...	...
Manufacturer / Brand	DAHUA	ATTE	PULSAR
Guarantee	3 years	3 years	2 years