



	<a href="#">IP CAMERA DS-2CD1T47G2H-LIU(2.8MM)PL ColorVu - 4 Mpx Hikvision</a>	<a href="#">RFID PROXIMITY CARD ATLO-308NR</a>
		
	876.00 PLN 876.00 PLN	4.44 PLN 4.44 PLN
Standard	...	13.56 MHz S50
Standard	IP	...
Compatibility	...	ISO/IEC 14443A
Possibility of programming the serial number (ID)	...	—
Ability to write to internal memory	...	192 B
Serial Number overprint	...	✓
Resolution	2560 x 1440 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	...
Sensor	1/3 " Progressive Scan CMOS	...
Lens	2.8 mm	...
View angle	115 °	...
White light LED illuminator range	50 m	...
Main features	...	<ul style="list-style-type: none"> <li>• Serial Number Format : 14H17D - Reverse number,</li> <li>• Range : ~ 10 cm ,</li> </ul>
Range of IR illumination	50 m	...
Memory card slot	—	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Audio transmission via network</li> </ul>	...
Main stream frame rate	20 fps @ 4 Mpx	...
Interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	6	...
ONVIF	✓	...

Main features	<ul style="list-style-type: none"> <li>• Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Horizontal mirror image</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Configurable Privacy Zones</li> <li>• Sharpness - sharper image outlines</li> <li>• video tampering</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> </ul>	...
Mobile phones support	<ul style="list-style-type: none"> <li>Port no.: 8000 or access by a cloud (P2P)</li> <li>• Android: Free application <a href="#">Hik-Connect</a></li> <li>• iOS: Free application <a href="#">Hik-Connect</a></li> </ul>	...
Default IP address	192.168.1.64	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	<ul style="list-style-type: none"> <li>• Main stream :</li> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li> <li>• Sub stream :</li> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 570 mA</li> </ul>	...
Power consumption	<ul style="list-style-type: none"> <li>• ≤ 8.3 W @ PoE</li> <li>• ≤ 6.8 W @ 12 V DC</li> </ul>	...
Housing	Compact, Metal	...
Color	White	...
"Index of Protection"	IP67	...
Mechanical protection class	—	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.41 kg	0.006 kg
Dimensions	202 x 84 x 81 mm	86 x 54 x 0.8 mm
Supported languages	Polish	...
Manufacturer / Brand	Hikvision	ATLO
SAP Code	311327308	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Guarantee	3 years	2 years
-----------	---------	---------



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00