



	IP CAMERA APTI-AI508C2IW-36AD Active Deterrence - 5 Mpx 3.6 mm	EXPANDER ZX-8 8 INPUTS PARADOX
		
	328.00 PLN 328.00 PLN	295.00 PLN 295.00 PLN
Standard	IP	...
Number of inputs	...	8 pcs - programmable
Support configurations	...	NO, NC, EOL, 2EOL, 3EOL
Output	...	1 pcs - 50 mA programmable
Main features	...	Automatic recognition of the alarm control panel model
Operation temp	...	-20 °C ... 50 °C
Resolution	2592 x 1944 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 720p	...
Sensor	1/2.8 " SONY Starvis™ Back-illuminated CMOS	...
Country of origin	...	Canada
Lens	3.6 mm	...
View angle	80 °	...
Range of IR illumination	25 m	...
White light LED illuminator range	25 m	...
Memory card slot	Micro SD memory cards up to 1TB support (possible local recording)	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	1 / 1	...
Audio	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in, • Bi-directional audio streaming support, • Audio transmission via network 	...
Main stream frame rate	max. 25 fps @ 5 Mpx	...
Interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	10	...
ONVIF	19.12	...

Intelligent image analysis	<ul style="list-style-type: none"> • intrusion - classification of people and vehicles • crossing the line (tripwire) - classification of people and vehicles • detection of people gathering • loitering detection • motion detection based on human detection 	...
Main features	<ul style="list-style-type: none"> • Active intrusion deterrence works by blinking blue and red light and siren sound or voice prompts • WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • Flicker Control - The technology eliminates the tiring eyes flickering image effect • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Smart motion detection (with recognizing people and vehicles) • Privacy zones - max. 3 • Image rotation and mirror • Day/Night mode - configurable • Sharpness - sharper image outlines 	...
Mobile phones support	<p>Port no.: 80 or access by a cloud (P2P)</p> <ul style="list-style-type: none"> • Android: Free application BitVision • iOS (iPhone): Free application BitVision 	...
Default IP address	192.168.1.168	...
Default admin user / password	admin / admin	...
Web browser access ports	80	...
PC client access ports	80	...
Mobile client access ports	80	...
Port ONVIF	80	...
RTSP URL	<p>rtsp://user:password@ip_address:80/0 - Main stream</p> <p>rtsp://user:password@ip_address:80/1 - Sub stream</p>	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 400 mA 	12 V ... 16 V DC / 28 mA (max)
Power consumption	≤ 4.8 W	...
Housing	Compact, Metal	...

Color	White	...
"Index of Protection"	IP67	...
Mechanical protection class	—	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.55 kg	0.052 kg
Dimensions	Ø 73 x 175 mm	140 x 46 mm
Supported languages	Polish, English, French, Russian, Spanish, Portuguese, Italian, Ukrainian, Hungarian	...
Manufacturer / Brand	APTI	PARADOX
Guarantee	2 years	2 years