

	<a href="#">PTZ OUTDOOR PTZ IP CAMERA DS-2CD1A43G0-IZU(2.8-12MM) - 3.7 Mpx 2.8 ... 12 mm Hikvision</a>	<a href="#">EXTENDER RECEIVER HDMI+USB-EX-100/RX SIGNAL</a>	<a href="#">SLEEVE AND EXPANSION ANCHORS KM-M10X80*P4</a>
			
	1111.00 PLN 1111.00 PLN	214.20 PLN 214.20 PLN	4.80 PLN 4.80 PLN
Standard	TCP/IP	...	...
Device type	...	Receiver	...
Sensor	1/3 " Progressive Scan CMOS	...	...
Matrix size	4 Mpx	...	...
In package	...	...	<b>4 pcs The price for package</b>
Screw	...	...	M10 x 80 mm
Drilling diameter	...	...	14 mm
Supported HDMI resolutions	...	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	...
Screw threading length	...	...	36 mm
Maximal transmission range	...	100 m UTP cat. 5e, 6	...
Sleeve diameter	...	...	13.5 mm
Protocols	...	HDBiT	...
Sleeve length	...	...	53 mm
Material	...	...	Steel galvanized
Resolution	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...	...
Application	...	...	Concrete, Solid clay brick
Lens	2.8 ... 12 mm	...	...
Operation temp	...	-10 °C ... 60 °C	...
Permissible relative humidity	...	20 % ... 90 % (non-condensing)	...
View angle	• 97 ° ... 30 ° (manufacturer data) • 94 ° ... 29 ° (our tests result)	...	...
Optical zoom	x 4	...	...
Digital zoom	—	...	...
Range of IR illumination	50 m	...	...
Video output	—	...	...
Horizontal rotation range	-100 ° ... 100 ° - Rotation of the head is limited by stops	...	...
Vertical rotation range	-20 ° ... 45 ° - Rotation of the head is limited by stops	...	...
RS-485 interface	—	...	...
Number of presets	—	...	...
Horizontal scan	—	...	...
Route settings	—	...	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...	...
Alarm inputs / outputs	—	...	...
Audio	• Microphone built-in, • Audio transmission via network, • Echo suppression and reduction / digital noise reduction, • Compliance with the AAC standard	...	...
Main stream frame rate	• 20 fps @ 4 Mpx • 25 fps @ 1080p	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Network interface	10/100 Base-T (RJ-45)	...	...
WEB Server	Built-in, NVR compliance	...	...
Max. number of on-line users	6	...	...
ONVIF	✓	...	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) • Android: Free application <a href="#">Hik-Connect</a> • iOS (iPhone): Free application <a href="#">Hik-Connect</a>	...	...
Default IP address	192.168.1.64	...	...
Default admin user / password	admin / - The administrator password should be set at the first start	...	...
Web browser access ports	80	...	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...	...
Mobile client access ports	8000	...	...
Port ONVIF	80	...	...
RTSP URL	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization	...	...
Main features	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronizes its</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• ICR - Movable InfraRed filter</li> <li>• Privacy zones - max. 4</li> <li>• Motion Detection</li> <li>• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect</li> <li>• Sharpness - sharper image outlines</li> <li>• Mirror - Mirror image</li> <li>• Day/night mode</li> </ul>	<ul style="list-style-type: none"> <li>• Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse</li> <li>• The devices do not require direct connection, they also operate via the LAN network</li> <li>• Audio transmission via network</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 920 mA</li> </ul>	5 V DC / 1 A (power adapter included)	...
Power consumption	<ul style="list-style-type: none"> <li>• ≤ 11 W @ 12 V DC</li> <li>• ≤ 12.5 W @ PoE</li> </ul>	...	...
Housing	PTZ, Metal + Plastic	...	...
Color	White	...	...
Operation temp	-30 °C ... 60 °C	...	...
"Index of Protection"	IP66	...	...
Weight	0.95 kg	0.168 kg	...
Dimensions	197 x 105 x 225 mm	110 x 89 x 26 mm	...
Supported languages	English, Ukrainian	...	...
Manufacturer / Brand	Hikvision	SIGNAL	...
SAP Code	311319374	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Guarantee	3 years	2 years	2 years
-----------	---------	---------	---------



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00