



	<a href="#">CONNECTOR FOR LED STRIPS AD-TL-6499/Z-P-Z/RGBW 12 mm ORNO</a>	<a href="#">IP SPEED DOME CAMERA OUTDOOR DS-2SE4C425MWG-E(14F0) TandemVu ColorVu - 3.7 Mpx 4.8 ... 120 mm Hikvision</a>
		
	2.01 USD 2.01 USD	1192.67 USD 1192.67 USD
Standard	...	TCP/IP
Application	Works with LED lighting RGBW	...
Number of power outputs	2 pcs	...
Strip width	12 mm	...
Length of the cable	140 mm	...
Maximal power voltage	48 V	...
Sensor	...	<ul style="list-style-type: none"> <li>• Camera PTZ : 1/3 " Progressive Scan CMOS,</li> <li>• Camera 2 : 1/2.8 " Progressive Scan CMOS</li> </ul>
Matrix size	...	<ul style="list-style-type: none"> <li>• Camera PTZ : 2.1 Mpx</li> <li>• Camera 2 : 3.7 Mpx</li> </ul>
Resolution	...	<ul style="list-style-type: none"> <li>• 2560 x 1440 - 3.7 Mpx,</li> <li>• 1920 x 1080 - 1080p</li> <li>• 1280 x 960 - 1.3 Mpx</li> <li>• 1280 x 720 - 720p</li> </ul>
Lens	...	<ul style="list-style-type: none"> <li>• Camera PTZ : 4.8 ... 120 mm</li> <li>• Camera 2 : 2.8 mm</li> </ul>
View angle	...	<ul style="list-style-type: none"> <li>• Camera PTZ : 55 ° ... 2.4 ° (manufacturer data) 53 ° ... 3 ° (our tests result),</li> <li>• Camera 2 : 96 ° (manufacturer data) 90 ° (our tests result)</li> </ul>
Optical zoom	...	x 25
Digital zoom	...	x 16
Range of IR illumination	...	100 m @ Camera PTZ
White light LED illuminator range	...	30 m @ Camera 2
Preset rotation speed	...	<ul style="list-style-type: none"> <li>• 80 °/s (horizontal)</li> <li>• 80 °/s (vertical)</li> </ul>
Rotation speed (manual control)	...	<ul style="list-style-type: none"> <li>• 0.1 °/s ... 80 °/s (horizontal)</li> <li>• 0.1 °/s ... 80 °/s (vertical)</li> </ul>
Horizontal rotation range	...	360 ° - continuous
Vertical rotation range	...	-15 ° ... 90 °
RS-485 interface	...	—
Number of presets	...	300

Horizontal scan	...	✓
Route settings	...	8
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	1 / 1
Audio	...	<ul style="list-style-type: none"> <li>• External microphone input</li> <li>• Audio output</li> <li>• Audio detection</li> <li>• Digital Noise Reduction</li> <li>• Compliance with the AAC standard</li> </ul>
Main stream frame rate	...	<ul style="list-style-type: none"> <li>• Camera PTZ : 25 fps @ 3.7 Mpx</li> <li>• Camera 2 : 25 fps @ 3.7 Mpx</li> </ul>
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	20
ONVIF	...	✓
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">Hik-Connect</a></li> <li>• iOS: Free application <a href="#">Hik-Connect</a></li> </ul>
Default admin user / password	...	admin / - The administrator password should be set at the first start
Default IP address	...	192.168.1.64
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> <li>• Camera PTZ - Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li> <li>• Camera 2 - Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/201/</li> </ul>



Main features	...	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• EIS - Electronic Image Stabilization</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• Day/night mode</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> <li>• Configurable: brightness, contrast, saturation</li> <li>• Parking action - this function enables to locate the camera to specific position automatically if operator doesn't operate the controller for some time</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support</li> <li>• Privacy zones</li> <li>• Intelligent 3D Positioning System</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, face detection</li> <li>• The camera is equipped with a built-in heater with a thermostat</li> </ul>
Power supply	...	<ul style="list-style-type: none"> <li>• PoE (802.3at),</li> <li>• 12 V DC / 3.33 A (power adapter included)</li> </ul>
Power consumption	...	≤ 24 W
Housing	Plastic	Speed Dome, Metal
Color	White	White + Black
Operation temp	...	-30 °C ... 65 °C
"Index of Protection"	—	IP66
Weight	0.002 kg	2.4 kg (without bracket)
Dimensions	140 x 15 x 5 mm	Ø 166 x 375 mm (without bracket)
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Vietnamese, Italian
Manufacturer / Brand	ORNO	Hikvision
SAP Code	...	327000910
Guarantee	2 years	3 years