



	USB SWITCH + HUB USB US-224 2 X 115 cm	IP CAMERA IPC2125SB-ADF28KMC-I0- BLACK Tri-Guard - 5 Mpx 2.8 mm UNIVIEW
		
	101.32 PLN 101.32 PLN	1120.00 PLN 1120.00 PLN
Standard	...	TCP/IP
Sensor	...	1/2.7 " Progressive Scan CMOS
Matrix size	...	5 Mpx
Connectors	<ul style="list-style-type: none"> • 2 x plug - USB 2.0 • 4 x socket - USB 2.0 • 1 x Power socket - mini USB 	...
Length of the cable	2 x 115 cm	...
USB standard	2.0	...
Main features	<ul style="list-style-type: none"> • LED indication • Support for platforms: Windows, Linux, Mac, Sun • Overload protection 	...
Resolution	...	2880 x 1620 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p
Lens	...	2.8 mm
View angle	...	<ul style="list-style-type: none"> • 113 ° (manufacturer data) • 104 ° (our tests result)
Range of IR illumination	...	30 m
White light LED illuminator range	...	30 m
S/N ratio	...	> 56 dB
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	...	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	<ul style="list-style-type: none"> • Microphone built-in • Speaker built-in • Audio detection • Bi-directional audio streaming support
Main stream frame rate	...	25 fps @ 5 Mpx
Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP PPPoE, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, IEEE 802.1x, SNMP, QoS, SSH

WEB Server	...	Built-in
Max. number of on-line users	...	32
ONVIF	...	✓
Mobile phones support	...	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address	...	DHCP or 192.168.1.13
Default admin user / password	...	admin / 123456
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream



Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • Active deterrence function - Light and sound alarm • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • Active deterrence function - Intelligent alarm linked to turning on white light and loudspeaker • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Image rotation and mirror • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines • Intelligent image analysis : intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area, face detection, people counting, crowd gathering estimation
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 960 mA
Power consumption	...	≤ 11.5 W
Housing	...	Compact, Metal + Plastic
Color	...	Black
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	0.14 kg	0.42 kg
Dimensions	83 x 77 x 25 mm	191 75 x 74 mm
Supported languages	...	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian
Manufacturer / Brand	ATEN	UNIVIEW
Guarantee	2 years	3 years