



	ROUTER RG-EW3200GXPRO Wi-Fi 6, 2.4 GHz, 5 GHz 800 Mbps + 2402 Mbps REYEE	IP CAMERA DS-2CD1067G2H-LIU(2.8MM) ColorVu - 6 Mpx Hikvision
		
	634.13 PLN 634.13 PLN	880.00 PLN 880.00 PLN
Standard	...	IP
Frequency range	2.4 GHz, 5 GHz	...
Antenna type	8 x Omnidirectional antenna - Integrated : • 6 dBi @ 5 GHz 4x4 MU-MIMO • 5 dBi @ 2.4 GHz 4x4 MU-MIMO	...
Resolution	...	3200 x 1800 - 6 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p
Sensor	...	1/2.4 " Progressive Scan CMOS
Lens	...	2.8 mm
Standards	IEEE 802.11 b/g/n @ 2.4 GHz , IEEE 802.11 a/n/ac/ax @ 5 GHz	...
View angle	...	115 °
Baud rates	800 Mbps + 2402 Mbps	...
White light LED illuminator range	...	30 m
Range of IR illumination	...	30 m
LAN ports	4 x 10/100/1000 Mbps LAN 1 x 10/100/1000 Mbps Uplink	...
Memory card slot	...	—
LED indicators	Status, Mesh	...
DDNS	✓	...
DHCP server	✓	...
Firmware update	✓	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	—
Protections	WPA/WPA2 Support DoS defence	...

Management interface	Web browser, Configuration using the Reyee Router application	...
Audio	...	<ul style="list-style-type: none"> • Microphone built-in, • Audio transmission via network
Main stream frame rate	...	20 fps @ 6 Mpx
Interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	6
Transmitter power	max. 20 dBm @ 2.4 GHz max. 27 dBm @ 5 GHz	...
ONVIF	...	—
Main features	...	<ul style="list-style-type: none"> • Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Possibility to change the resolution, quality and bit rate • Horizontal mirror image • Smart motion detection (with recognizing people and vehicles) • Configurable Privacy Zones • Sharpness - sharper image outlines • video tampering • Filtering of false alarms based on the recognition of persons and vehicles
Mobile phones support	Android: Free application Reyee Router iOS (iPhone): Free application Reyee Router	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default IP address	...	192.168.1.64
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80

Main features	<ul style="list-style-type: none"> • Support for Reyee Mesh technology, • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • Static / dynamic routing • Built-in 4-port switch • Access Point • QoS • Remote management • DMZ • UPnP • Support for dynamic ARP mapping and static table • Port forwarding • Port Mapping • parental control • Guest Network - a separate and secure network for guests • DHCP client list • SSID hiding • IPv6 compliance • PPTP VPN Server / Client 	...
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	8000
Operation temp	0 °C ... 45 °C	...
Port ONVIF	...	80
Permissible relative humidity	5 % ... 95 % (non-condensing)	...
RTSP URL	...	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/
Power supply	12 V DC / 2.5 A (power adapter included)	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 550 mA
Power consumption	≤ 36 W	<ul style="list-style-type: none"> • ≤ 8 W @ PoE • ≤ 6.6 W @ 12 V DC
Housing	...	Compact, Metal
Color	...	White
"Index of Protection"	...	IP67
Mechanical protection class	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	0.77 kg	0.3 kg

Dimensions	230 x 230 x 162 mm	Ø 70 x 173 mm
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand	RUIJIE / REYEE	Hikvision
SAP Code	...	311325494
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00