




	SWITCH POE APTI-POE0402-60W 4-PORT	OPTICAL LIGHT SOURCE SP-OSM32/MINI 1310 / 1550 nm Spacetronek
		
	152.00 PLN 152.00 PLN	384.00 PLN 384.00 PLN
Optical wavelength	...	1310 / 1550 nm
Optical output power	...	≥ -7 dBm
LAN ports	6 x RJ45 (4 x IEEE 802.3af)	...
Connector type	...	Sleeve 2.5 mm
Material	...	Plastic
Management	—	...
LED diodes	LAN, WAN, PoE	...
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 Mbps : 2 x Port LAN, • 10 / 100 Mbps : 4 x LAN & PoE ports 	...
Maximal output power	15.4 W / port PoE	...
Maximal total power	60 W	...
MAC addresses table	2k	...
Main features	<ul style="list-style-type: none"> • 2 x Port Uplink • Range PoE : 200 m - The EXTEND mode enabled 	<ul style="list-style-type: none"> • Good output power stability • Large, readable LCD display with backlight • Automatic power-off • Battery charge indicator • The universal connector allows to connect all optical connectors of 2.5 mm standard, eg SC/FC/ST • High durability tool, made from high quality materials • The set includes adapters SC / FC / ST • The device works with both single-mode and multi-mode fibers • Small dimensions • The set includes a practical case • Backup time : 40 h
Certificates	CE	...
Power supply	230 V AC	3 x 1.5 V - Battery type LR3 (AAA) (not included)
Operation temp	0 °C ... 55 °C	...
Weight	0.65 kg	0.13 kg - Without batteries

Dimensions	220 x 141 x 41 mm	132 x 65 x 29 mm
Manufacturer / Brand	APTI	Spacetronek
Guarantee	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00