

	<a href="#">AHD, HD-CVI, HD-TVI CAMERA BCS- EA25FSR3(H2) - 5 Mpx 2.8 mm</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE76H0T- ITPFS(2.8mm) - 5 Mpx Hikvision</a>
	190.00 PLN 190.00 PLN	258.00 PLN 258.00 PLN
Standard	AHD / HD-CVI / HD-TVI / CVBS	AHD / HD-CVI / HD-TVI / CVBS
Matrix size	...	5 Mpx
Sensor	1/2.8 " Progressive Scan CMOS	Progressive Scan CMOS
Resolution	2704 x 1950 - 5 Mpx @ AHD / HD-TVI @ 20 fps , 2560 x 1440 - 3.7 Mpx @ AHD / HD-CVI / HD-CVI @ 25 fps 1920 x 1080 - 1080p - AHD, HD-TVI, HD-CVI @ 25 fps	<ul style="list-style-type: none"> <li>• 2560 x 1944 - 5 Mpx @ AHD / HD-TVI - 20 fps</li> <li>• 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI - 25 fps</li> <li>• 1920 x 1080 - 1080p @ HD-TVI - 25 fps</li> <li>• 960 x 576 - 960H @ PAL</li> </ul>
IR illuminator power adjustment	...	Automatic
Range of IR illumination	30 m	20 m
Lens	2.8 mm, F1.2	2.8 mm
S/N ratio	> 50 dB	...
View angle	103 °	86 °
IR illuminator support	...	ICR - Movable InfraRed filter
Video output	AHD / HD-CVI / HD-TVI, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio output</li> </ul>	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio support via coaxial cable</li> </ul>

Main features	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• BLC - configurable Back Light Compensation</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• HLC - High Light Compensation (spot)</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> </ul>	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• AGC - Automatic Gain Control</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> </ul>
Mechanical protection class	—	...
OSD menu	✓	OSD menu available via recorder
Power supply	12 V DC / 420 mA	12 V DC / 310 mA
Power consumption	< 5 W	≤ 3.7 W
Housing	Dome, Metal	Dome, Plastic
Color	White	White
"Index of Protection"	IP66	—
Vandal-proof	...	—
Operation temp	-20 °C ... 60 °C	-40 °C ... 60 °C
Weight	0.3 kg	0.15 kg
Dimensions	Ø 94 x 80 mm	Ø 85 x 79 mm
Manufacturer / Brand	BCS	Hikvision
SAP Code	...	300613327
Guarantee	3 years	3 years