



	<a href="#">IP CAMERA APTI-42MP-37 PINHOLE - 4 Mpx 3.7 mm</a>	<a href="#">SCREWS FOR MOUNTING FIBER OPTIC ADAPTERS SM-AD*P100</a>
		
	326.40 PLN 326.40 PLN	11.49 PLN 11.49 PLN
Standard	TCP/IP	...
Sensor	1/3 " Progressive Scan CMOS	...
Matrix size	4 Mpx	...
In package	...	<b>100 pcs The price for package</b>
thread	...	Ø 2.2 x 9.5 mm
Resolution	2688 x 1512 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Lens	3.7 mm (pinhole)	...
View angle	• 70 ° (manufacturer data) • 90 ° (our tests result)	...
S/N ratio	60 dB	...
Min. illumination	0.01 Lux @ F1.6 (AGC off)	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Main stream frame rate	25 fps - 4 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, SMTP, UDP	...
Audio	• Microphone built-in • Audio transmission via network	...
ONVIF	2.4	...
RS-485 interface	—	...
Memory card slot	Micro SD memory cards up to 512GB support (possible local recording)	...
Mobile phones support	Port no.: 80 or access by a cloud (P2P) • Android: Free application <a href="#">BitVision</a> • iOS (iPhone): Free application <a href="#">BitVision</a>	...
Default IP address	192.168.1.168	...
Default admin user / password	admin / admin	...
Web browser access ports	80	...
PC client access ports	80	...

WEB Server	Built-in Built-in	...
Mobile client access ports	80	...
Max. number of on-line users	10 10	...
Port ONVIF	80	...
RTSP URL	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream	...
Main features	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• Flicker Control - The technology eliminates the tiring eyes flickering image effect</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Motion Detection</li> <li>• Privacy zones</li> <li>• Configurable: brightness, contrast, saturation</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> <li>• Intelligent image analysis : intrusion</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 170 mA</li> </ul>	...
Power consumption	≤ 2.1 W	...
Housing	Mini - Metal	...
Color	Black	...
Operation temp	-20 °C ... 60 °C	...
Weight	0.12 kg	...
Dimensions	37.5 x 37.5 x 30 mm	Ø 3.9 x 10.9 mm
Supported languages	Polish, English, Bulgarian, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian	...
Manufacturer / Brand	APTI	...
Guarantee	2 years	...