




	OMNIDIRECTIONAL ANTENNA ATK-D2/SMA	ACCESS CONTROLLER MODULE MC16-PAC-EX-5 ROGER	PLUG WT-55/KAT-1.5M
			
	63.88 PLN 63.88 PLN	4320.00 PLN 4320.00 PLN	8.33 PLN 8.33 PLN
Number of served transitions	...	5	...
Inputs	...	30	...
Outputs	...	20	...
Connector type	Ø 2.1 / 5.5 mm Angular plug
Wire mounting	Soldering
Frequency range	806 ... 960 MHz 1710 ... 2500 MHz
Number of users	...	max. 12000 - Number of identifiers	...
Length of the cable	1.5 m
Application	Electric cable
Connector	SMA-RP Plug
Number of media per ID	...	8 - Proximity card, PIN code, fingerprint, etc.	...
Material	PET
Gain	max. 3 dB
Number of permissions per ID	...	100	...
Impedance	50 Ω
Buffer memory	...	8 000 000 events buffer	...
Polarization	Vertical
MCT readers support	...	16 pcs	...
Example of application	<ul style="list-style-type: none"> • OMY-2X0.75 • K-60 • YAP
Readers connections	...	4 pcs - Wiegand / PRT	...
Number of login points	...	10	...
Number of access terminals	...	20	...
Number of access zones	...	10	...
Number of alarm zones	...	10	...
Number of automation nodes	...	10	...
Battery backup support	...	12 V / 7 Ah	...

Communication	...	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RS-485 interface • RACS 5 v2 (Roger) 	...
Main features	<ul style="list-style-type: none"> • Small dimensions 	<ul style="list-style-type: none"> • Integrated support in VISO EX software • Functions in the VISO EX system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system - unlimited - division of the system into partitions operated by independent operators - tool for integration with RACS5 (API) systems - integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems) 	...
Power supply	...	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	...
Operation temp	...	5 °C ... 40 °C	...
Permissible relative humidity	...	10 % ... 95 % (non-condensing)	...
Weight	0.150 kg	0.14 kg	0.020 kg
Dimensions	Ø 165 x 94 mm	175 x 72 x 30 mm	...
Manufacturer / Brand	...	ROGER	...
Guarantee	2 years	3 years	2 years