



	<a href="#">VIDEO SPLITTER RV-1/4P</a>	<a href="#">ACCESS CONTROLLER ASI3213G-MW DAHUA</a>
		
	79.54 PLN 79.54 PLN	2063.00 PLN 2063.00 PLN
Sensor	...	CMOS
Number of inputs	1 pcs BNC	...
Matrix size	...	2 Mpx
Number of outputs	4 pcs BNC	...
Bandwidth	0 ... 40 MHz (-3dB)	...
Inputs impedance	75 Ω	...
Resolution	...	1920 x 1080 - 1080p
Outputs impedance	75 Ω	...
Current consumption	60 mA	...
Gain	0 dB	...
Standard	CVBS - PAL / NTSC	TCP/IP
IR illuminator	...	✓
LED illuminator	...	✓
Temperature measurement	...	—
Temperature measurement range	...	—
Accuracy of temperature measurement	...	—
Face recognition distance	...	0.3 m ... 1.5 m (max 1500 faces in the database)
RFID proximity reader built-in	...	<ul style="list-style-type: none"> <li>• 13.56 MHz S50</li> <li>• Memory of 1500 RFID cards</li> </ul>
Internal memory	...	Support storage of 150 000 records
Video output	...	—
RS-485 interface	...	✓
RS-232 interface	...	—
Wiegand interface	...	—
USB	...	1 x USB 2.0
Memory card slot	...	—
Alarm inputs / outputs	...	1 / 1 - Relay outputs
Audio	...	Voice message
Network interface	...	1 x 10/100 Base-T (RJ-45)
Network protocols	...	IPv4, RTSP, RTP, TCP, UDP, P2P
WEB Server	...	Built-in
ONVIF	...	—

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Default IP address	...	192.168.1.108
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Main features	...	<ul style="list-style-type: none"> <li>• Built-in LCD display showing the image from the video camera - 4.3 " capacitive touch screen, 480 x 272 px</li> <li>• Identification modes : PIN, Proximity identifier 13.56 MHz S50, Face recognition, Any combination of the above</li> <li>• 1500 users</li> <li>• Software update via network</li> <li>• Real-time Surveillance</li> <li>• Multiple Authentication</li> <li>• Take face image after swiping card</li> <li>• Auto-Registration</li> <li>• Backup to USB drive (pendrive, external drive)</li> <li>• Output button support</li> <li>• Door status detection</li> <li>• Lock control</li> <li>• Function to prevent of multiple use of the same code/card to gain access (anti-passback)</li> <li>• Auto-uploads alarm messages to Master or client station after entering the duress code to open the door</li> <li>• Ability to work with reed switch and signalling the door being opened too long</li> <li>• 128 General Purpose Schedules</li> <li>• Unlocking the transition only when more than one user is present</li> <li>• Tamper protections</li> </ul>
Power supply	12 V DC (power adapter not included)	12 V DC / 1.5 A (power adapter included)
Power consumption	...	≤ 18 W

Housing	...	Plastic (ABS)
Color	...	Black + Silver
"Index of Protection"	...	—
Operation temp	...	-10 °C ... 55 °C
Weight	0.098 kg	<ul style="list-style-type: none"> <li>• 0.22 kg (without stand)</li> <li>• 0.24 kg (with stand)</li> </ul>
Dimensions	117 x 30 x 80 mm	<ul style="list-style-type: none"> <li>• 116 x 107 x 22 mm (without stand)</li> <li>• 116 x 107 x 78 mm (with stand)</li> </ul>
Supported languages	...	English
Manufacturer / Brand	DELTA	DAHUA
Guarantee	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00