



	IP CAMERA IPC-HDW1530T-0360B-S6 - 5 Mpx 3.6 mm DAHUA	CEE-CONNECTOR PCE-2246 400 V 32 A 4P 6H IP44 / IP54
		
	799.00 PLN 799.00 PLN	28.72 PLN 28.72 PLN
Standard	TCP/IP	...
Sensor	1/2.7 " Progressive Scan CMOS	...
Rated voltage	...	400 V / 50 ... 60 Hz
Scanning system	Progressive	...
Maximal current load	...	32 A
Matrix size	5 Mpx	...
Number of poles	...	4P
Grounding	...	6h
Electrical cable	...	max. 4 x 6 mm ²
Cable terminals	...	screw terminals
Plug type	...	CEE
Contact material	...	CuZn
Maximum wire insulation diameter	...	20 mm
Resolution	2880 x 1620 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	...
Lens	3.6 mm	...
View angle	• 92 ° (manufacturer data) • 87 ° (our tests result)	...
Range of IR illumination	30 m	...
S/N ratio	> 56 dB	...
Memory card slot	—	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Audio	Microphone built-in	...
Main stream frame rate	20 fps @ 5 Mpx 25 fps @ 4 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, SMTP, FTP, DHCP, DNS, DDNS, NTP, Multicast	...
WEB Server	Built-in	...
Max. number of on-line users	20	...
ONVIF	20.06	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Motion Detection • Configurable Privacy Zones • D-ZOOM - Digital Zoom • Mirror - Mirror image 	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS 	...
Default IP address	192.168.1.108	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Color	White	Red
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 500 mA 	...
Power consumption	<ul style="list-style-type: none"> • ≤ 4.5 W @ PoE • ≤ 3.7 W @ 12 V DC 	...
Housing	Dome - Metal	...
"Index of Protection"	IP67	IP44 / IP54
Operation temp	-40 °C ... 60 °C	...
Dimensions	Ø 94 x 85 mm	161 x 94 x 67 mm
Weight	0.33 kg	0.25 kg
Supported languages	English, Spanish, Russian	...
Manufacturer / Brand	DAHUA	PCE
Guarantee	3 years	2 years

