



	ACCESS POINT UNIFI-UAP-AC-PRO UBIQUITI	ACCESS CONTROLLER ASI1212F DAHUA
		
	803.06 PLN 803.06 PLN	944.00 PLN 944.00 PLN
Cards support	...	13.56 MHz S50
Reading distance of prox-keys	...	1 ... 3 cm
Keyboard built-in	...	—
Autonomous operation	...	✓
Frequency range	• 5150 MHz ... 5875 MHz, • 2412 MHz ... 2462 MHz	...
Battery backup support	...	—
Input lines	...	3
Output lines	...	3
Identification time	...	< 1.5 s
Antenna type	3Tx 3Rx MIMO, 2.4 GHz / 5.0 GHz - 3 dBi, Integrated - 3 x Omnidirectional antenna	...
Communication	...	• RS-485 • Wiegand • LAN
RS-485 interface	...	✓
RS-232 interface	...	—
Wiegand interface	...	✓
Network interface	...	10/100 Base-T
Default IP address	...	192.168.1.108
Standards	• IEEE 802.11ac, • IEEE 802.11b, • IEEE 802.11g, • IEEE 802.11n	...
Default admin user / password	...	admin / - The administrator password should be set at the first start
USB	...	—
Memory card slot	...	—
Baud rates	• 1300 Mbps @ 5 GHz, • 450 Mbps @ 2.4 GHz	...
Internal memory	...	Support storage of 150 000 records

Wireless transmission range	122 m	...
Protections	WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES)	...
LAN ports	2 x 10/100/1000 Mbps BASE-TX (Cat. 5, RJ-45)	...
Operating system	UniFi WiFi Enterprise System	...
Transmitter power	<ul style="list-style-type: none"> • 22 dBm @ 2.4 GHz (max) • 22 dBm @ 5.0 GHz (max) 	...
Power supply PoE	44 V ... 57 V - Ubiquiti Passive PoE, PoE (802.3af/at)	...
Power supply	48 V / 0.5 A - PoE Adapter - included	12 V DC / 1 A
Power consumption	9 W	...
Main features	<ul style="list-style-type: none"> • Possibility to mount on the wall or ceiling • UniFi WiFi Enterprise System • AP placement and RF maps • Easy and uniform management system for many devices • Intuitive installation and configuration of many advanced functions 	<ul style="list-style-type: none"> • Built-in LCD display 240 x 320 px - 2.8 " capacitive touch screen • Fingerprint reader built-in • Memory of 3000 fingerprint patterns • Possible connection of the external ASR series reader (read in/out door control) • Identification modes : Proximity identifier 13.56 MHz S50, Fingerprint, PIN, Any combination of the above • Remote access verification • Tamper detection - removing from mounting surface • Support for door contact and exit button • Indication of forced entry and the lack of closing doors • 30000 indexed users • Possibility to configure access groups • 128 General Purpose Schedules • 128 time periods within single Schedule • Holiday Schedules • Anti-passback • Integration with an alarm system via in/out line • Remote programming from PC

"Index of Protection"	...	—
Operation temp	-10 °C ... 70 °C	-10 °C ... 45 °C
Permissible relative humidity	5 % ... 95 %	5 ... 90 % (non-condensing)
Dimensions	Ø 197 x 36.5 mm	115 x 115 x 32 mm
Weight	<ul style="list-style-type: none"> • 0.33 kg • 0.47 kg (with mounting kits) 	0.22 kg
Supported languages	...	English
Manufacturer / Brand	UBIQUITI	DAHUA
Guarantee	2 years	3 years