



	EXTENDER RECEIVER HDMI-EX-120/RX-V4	IP CAMERA DS-2CD2T47G2-LSU/SL(2.8MM)(C) ColorVu - 4 Mpx Hikvision
		
	254.40 PLN 254.40 PLN	1782.00 PLN 1782.00 PLN
Standard	...	TCP/IP
Device type	Receiver	...
Sensor	...	1/1.8 " Progressive Scan CMOS
Matrix size	...	4 Mpx
Supported HDMI resolutions	480i, 576i, 480p, 576p, 720p, 1080i, 1080p	...
Maximal transmission range	• 100 m UTP cat. 5e • 120 m UTP cat. 6	...
Resolution	...	2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p
Protocols	HdbitT	...
Lens	...	2.8 mm
Max. number of receivers working in the same time	237	...
Supported HDMI standard	1.3	...
HDCP	1.4	...
View angle	...	• 112 ° (manufacturer data) • 100 ° (our tests result)
White light LED illuminator range	...	60 m
Memory card slot	...	Micro SD memory cards up to 512GB support (possible local recording)
Operation temp	0 °C ... 60 °C	...
Permissible relative humidity	10 % ... 90 % (non- condensing)	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	1 / 1
Audio	...	• Microphone built-in, • External microphone input • Audio output • Bi-directional audio streaming support • Compliance with the AAC standard
Main stream frame rate	...	25 fps @ 4 Mpx
Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, IEEE 802.1x, QoS, IPv4/IPv6, UDP, Bonjour, SSL / TLS, PPPoE, SNMP, ARP, WebSocket, WebSockets
WEB Server	...	Built-in

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Max. number of on-line users	...	6
ONVIF	...	19.12
Main features	...	<ul style="list-style-type: none"> • Active deterrence function - Light and sound alarm • Possibility to turn off the LED illuminator • WDR - 130 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • Possibility to change the resolution, quality and bit rate • Horizontal mirror image • Smart motion detection (with recognizing people and vehicles) • Configurable Privacy Zones • Sharpness - sharper image outlines • video tampering • Filtering of false alarms based on the recognition of persons and vehicles • Intelligent image analysis : crossing the line (tripwire), intrusion, scene changing, detection of entry into the area / exit from the area - classification of people and vehicles, face detection
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default IP address	...	192.168.1.64
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/
Power supply	5 V DC / 1 A (power adapter included)	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 660 mA
Power consumption	...	<ul style="list-style-type: none"> • ≤ 9 W @ PoE • ≤ 8 W @ 12 V DC



Housing	...	Compact, Aluminum alloy + Plastic
Color	...	White
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	0.13 kg	1.18 kg
Dimensions	110 x 58 x 26 mm	289 x 105 x 105 mm
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand	...	Hikvision
SAP Code	...	311316084
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00