


	<a href="#">IP CAMERA IPC2125SB-ADF28KMC-I0</a> <a href="#">Tri-Guard - 5 Mpx 2.8 mm UNIVIEW</a>
	
	319.62 EUR 319.62 EUR
Standard	TCP/IP
Sensor	1/2.7 " Progressive Scan CMOS
Matrix size	5 Mpx
Resolution	2880 x 1620 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p
Lens	2.8 mm
View angle	<ul style="list-style-type: none"> <li>• 113 ° (manufacturer data)</li> <li>• 105 ° (our tests result)</li> </ul>
Range of IR illumination	30 m
White light LED illuminator range	30 m
S/N ratio	> 52 dB
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	—
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Speaker built-in</li> <li>• Audio detection</li> <li>• Bi-directional audio streaming support</li> </ul>
Main stream frame rate	25 fps @ 5 Mpx
Network interface	10/100 Base-T (RJ-45)
Network protocols	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, IEEE 802.1x, SNMP, QoS, SSH
WEB Server	Built-in
Max. number of on-line users	32
ONVIF	✓
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EZView</a></li> <li>• iOS (iPhone): Free application <a href="#">EZView</a></li> </ul>
Default IP address	DHCP or 192.168.1.13

Default admin user / password	admin / 123456
Web browser access ports	80, 554
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>
Mobile client access ports	80
Port ONVIF	80
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream
Main features	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support</li> <li>• Active deterrence function - Intelligent alarm linked to turning on white light and loudspeaker</li> <li>• Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Image rotation and mirror</li> <li>• Privacy zones - max. 4</li> <li>• Motion detection with human/vehicle silhouette recognition</li> <li>• Sharpness - sharper image outlines</li> <li>• Intelligent image analysis : intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area, face detection, people counting, crowd gathering estimation</li> </ul>
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 960 mA</li> </ul>
Power consumption	≤ 11.5 W
Housing	Compact, Metal + Plastic
Color	White
"Index of Protection"	IP67
Vandal-proof	—

Operation temp	-30 °C ... 60 °C
Weight	0.42 kg
Dimensions	191 75 x 74 mm
Supported languages	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian
Manufacturer / Brand	UNIVIEW
Guarantee	3 years