



| | SMART LED LIGHTING CONTROLLER WLIGHTBOX-V3/BLEBOX Wi-Fi, 12 ... 24 V DC | SMART LIGHTING DIMMER DIMMERBOX-V2/BLEBOX Wi-Fi, 230 V AC |
|-----------------------|--|--|
| |  |  |
| | 123.65 PLN 123.65 PLN | 152.93 PLN 152.93 PLN |
| Application | Works with LED lighting - (RGB/RGBW/RGBCCT/CCT/MONO) 12-24V LED strips | lighting brightness control |
| Rated voltage | 12 ... 24 V DC | 230 V AC |
| Maximal total load | 360 W | <ul style="list-style-type: none"> • 250 W (resistance load), • 30 W (inductive or capacitive load - e.g. LED lamp) |
| Total maximal current | 15 A (3 A / Channel) | 1.1 A |
| Number of inputs | 1 | 2 |
| Number of outputs | 5 | 1 |
| Connector type | screw terminals | screw terminals |
| Wireless | Wi-Fi, 2.4 GHz - IEEE 802.11g | Wi-Fi, 2.4 GHz - IEEE 802.11g |
| Mobile phones support | <ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS | <ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS |

| | | |
|-----------------------|---|--|
| Main features | <ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • Controlling the color, color temperature, brightness, effect, changing time allows any interior arrangement • predefined effects, • effects modification, • Operation modes : <ul style="list-style-type: none"> - 1 x RGB (color) - 1 x RGBW (color + white - brightness control) - 1 x RGBWW / RGB CCT (color + white - brightness and color temperature control) - 1 x RGB (color) + 1 x MONO (single color) - 1 x CCT (white - brightness and color temperature control) - 2 x CCT (white - brightness and color temperature control) - 1 x RGB (color) + 1 x CCT (white - brightness and color temperature control) - 5 x MONO (single color) / halogen bulb • µWiFi technology support | <ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • remote access, • voice control, • The ability to set the default status of the device after a power failure, • µWiFi technology support |
| Housing | Plastic | Plastic |
| "Index of Protection" | IP20 | IP20 |
| Color | Black | Black |
| Operation temp | -20 °C ... 50 °C | -20 °C ... 50 °C |
| Weight | 0.026 kg | 0.04 kg |
| Dimensions | 43 x 35 x 18 mm | 41 x 39 x 24 mm |
| Manufacturer / Brand | BleBox | BleBox |
| Guarantee | 2 years | 2 years |