




	<a href="#">IP SPEED DOME CAMERA OUTDOOR IPC6424SR-X25-VF-B - 4 Mpx 4.8 ... 120 mm UNIVIEW</a>	<a href="#">SMART ROLLER GATE CONTROLLER ROLLERGATE/BLEBOX Wi-Fi, 230 V AC</a>
		
	4442.26 PLN 4442.26 PLN	365.06 PLN 365.06 PLN
Application	...	roller gates
Standard	TCP/IP	...
Rated voltage	...	230 V AC
Sensor	1/2.8 " Progressive Scan CMOS	...
Maximal total load	...	2 x 1250 VA
Matrix size	4 Mpx	...
Total maximal current	...	2 x 5 A
Number of inputs	...	<ul style="list-style-type: none"> <li>• 4 control,</li> <li>• 2 security</li> </ul>
Number of outputs	...	<ul style="list-style-type: none"> <li>• 2 control,</li> <li>• 1 signaling</li> </ul>
Connector type	...	screw terminals
Resolution	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	...
Lens	4.8 ... 120 mm	...
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11g
View angle	<ul style="list-style-type: none"> <li>• 52 ° ... 2.7 ° (manufacturer data)</li> <li>• 52 ° ... 3.1 ° (our tests result)</li> </ul>	...
Optical zoom	x 25	...
Digital zoom	x 16	...
Range of IR illumination	100 m	...
Video output	1 Vpp / 75 Ω - BNC plug	...
Preset rotation speed	<ul style="list-style-type: none"> <li>• 240 °/s (horizontal)</li> <li>• 200 °/s (vertical)</li> </ul>	...
Rotation speed (manual control)	<ul style="list-style-type: none"> <li>• 0.1 °/s ... 200 °/s (horizontal),</li> <li>• 0.1 °/s ... 120 °/s (vertical)</li> </ul>	...
Horizontal rotation range	360 ° - continuous	...
Vertical rotation range	-15 ° ... 90 °	...

Main features	...	<ul style="list-style-type: none"> <li>• Roller gate control in cooperation with security modules (photocell, barrier, sensing edge),</li> <li>• Multiple users support from anywhere,</li> <li>• Control many objects from one app,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Keyboard built-in - 3 Touch control keys,</li> <li>• Backlit, touch control panel</li> <li>• Omnidirectional antenna</li> <li>Wi-Fi 5 dB,</li> <li>• SMA-RP socket</li> <li>• Range : 100 m (in open area), 40 m (internal)</li> <li>• µWiFi technology support</li> </ul>
RS-485 interface	✓	...
Number of presets	1024	...
Horizontal scan	—	...
Route settings	16	...
Image compression method	Ultra H.265 / H.265 / H.264 / MJPEG	...
Operation temp	...	-20 °C ... 50 °C
Alarm inputs / outputs	2 / 1	...
Audio	<ul style="list-style-type: none"> <li>• Audio input</li> <li>• Audio output</li> <li>• Bi-directional audio streaming support</li> <li>• Audio detection</li> <li>• Noise reduction</li> </ul>	...
Main stream frame rate	1 ... 30 fps @ 4 Mpx	...
Network interface	10/100 Base-TX (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	32	...
ONVIF	✓	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EZView</a></li> <li>• iOS (iPhone): Free application <a href="#">EZView</a></li> </ul>	<ul style="list-style-type: none"> <li>• The <a href="#">wBox</a> free application on Android</li> <li>• The <a href="#">wBox</a> free application on iOS</li> </ul>
Default IP address	DHCP or 192.168.1.13	...
Default admin user / password	admin / 123456	...
Web browser access ports	80, 554	...
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>	...

Mobile client access ports	80	...
Port ONVIF	80	...
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	...
Main features	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• Configurable Privacy Zones - 24</li> <li>• Motion Detection</li> <li>• Tamper signaling</li> <li>• Image rotation and mirror</li> <li>• Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, Filtering of false alarms based on the recognition of persons and vehicles, face detection - supports 4 types of facial attributes extraction, counting people entering and leaving the area, crowd gathering estimation</li> <li>• Intelligent Object Tracking</li> </ul>	...
Housing	Speed Dome, Metal + Plastic	Self-extinguishing , Surface-mounted (box)
Color	White + Black	Gray / Black
"Index of Protection"	IP67	IP44
Vandal-proof	IK10	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3at),</li> <li>• 12 V DC / 3 A (power adapter included)</li> </ul>	...
Power consumption	≤ 21 W	...
Operation temp	-40 °C ... 70 °C	...
Weight	4.02 kg (with bracket)	0.37 kg
Dimensions	Ø 166 x 280 x 378 mm (with bracket)	<ul style="list-style-type: none"> <li>• 129 x 96 x 57 mm - without antenna</li> <li>• 285 x 96 x 57 mm - with antenna, vertical</li> <li>• 197 mm - Antenna</li> </ul>

Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovenian, Hungarian, Italian	...
Manufacturer / Brand	UNIVIEW	BleBox
Guarantee	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00