


	IP CAMERA BCS-V-TIP45VSR5 - 5 Mpx 2.8 ... 12 mm - MOTOZOOM BCS View	SWITCHING ADAPTER EDR-150-24 MEAN WELL
		
	1350.00 PLN 1350.00 PLN	138.70 PLN 138.70 PLN
Adapter type	...	Switching
Standard	TCP/IP	...
Sensor	1/2.7 " Progressive Scan CMOS	...
Matrix size	5 Mpx	...
Power voltage	...	<ul style="list-style-type: none"> • 90 ... 264 V AC • 127 ... 370 V DC
Output voltage	...	24 V DC
Output voltage adjustment	...	24 ... 28 V DC
Maximal load	...	6.5 A
Output power	...	156 W
Number of outputs	...	1 pcs
Efficiency	...	87 %
Resolution	2560 x 1920 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	...
Housing type	...	DIN
Lens	2.8 ... 12 mm - Motozoom	...
View angle	97 ° ... 30 °	...
Protections	...	<ul style="list-style-type: none"> • Short-circuit • Overload • Overvoltage • Overheat
Operation temp. / Relative humidity	...	-20 °C ... 60 °C / 20 ... 95 %
Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Range of IR illumination	50 m	...
Audio	—	...
Alarm inputs / outputs	—	...
Main stream frame rate	<ul style="list-style-type: none"> • 20 fps - 5 Mpx • 25 fps - 3.7 Mpx 	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, IEEE 802.1x, QoS, IPv4, IPv6, Bonjour, UDP, SSL / TLS	...
WEB Server	Built-in	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...

Max. number of on-line users	6	...
ONVIF	✓	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager	...
Default IP address	192.168.1.64	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P)	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/	...
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • ROI - improve the quality of selected parts of image • 3D-DNR - Digital Noise Reduction • AGC - Automatic Gain Control • Auto White Balance • ICR - Movable InfraRed filter • BLC - configurable Back Light Compensation • Day/Night mode (color/b&w/auto) • Motion Detection • Configurable Privacy Zones • Mirror - Mirror image • Sharpness - sharper image outlines 	...
Power supply	• PoE (802.3af), • 12 V DC / 915 mA	...
Power consumption	• ≤ 12.9 W @ PoE (802.3at) • ≤ 11 W @ 12 V DC	...
Housing	Compact, Metal	...
Color	White	...
"Index of Protection"	IP67	...
Vandal-proof	—	...
Operation temp	-30 °C ... 60 °C	...
Supported languages	Polish, English	...
Weight	0.75 kg	0.51 kg
Dimensions	Ø 105 x 244 mm	127 x 126 x 41 mm
Manufacturer / Brand	BCS View	MEAN WELL
Guarantee	3 years	2 years