

	SMART DUAL VALVE FOR THE IRRIGATION SYSTEM ATLO-VR2G-BLE-TUYA Bluetooth BLE, Tuya Smart	NVR NVR504-32B 32 CHANNELS UNIVIEW
		
	214.80 PLN 214.80 PLN	3276.90 PLN 3276.90 PLN
Standard	...	TCP/IP
Application	irrigation control - 2 Zones	...
Type (size)	3/4 "	...
Supported resolutions	...	max. 16 Mpx - 4608 x 3472 px
Video outputs	...	1 pcs HDMI 4K 1 pcs VGA There is a possibility to configure a SPOT function on one of the output
Working pressure	0.05 ... 0.8 MPa / 7.25 ... 116 psi	...
Audio support	...	<ul style="list-style-type: none"> • 32 Channels - Audio from cameras • Bi-directional audio streaming support • Audio detection
Opening/closing time	5 ... 10 s	...
Audio inputs	...	1 pcs CINCH
Audio outputs	...	1 pcs CINCH
Image compression method	...	Ultra 265 / H.265 / H.264
Bitrate	...	max. 320 Mbps
Wireless	<ul style="list-style-type: none"> • Bluetooth, • 2.4 GHz Wi-Fi IEEE 802.11 b/g/n - Bluetooth/Wi-Fi gateway 	...
Supported hard drives	...	4 x 8 TB SATA
Recording modes	...	Manual, Sensor, Motion detection, Schedule
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Radio communication range (at open area)	<ul style="list-style-type: none"> • 15 m - Bluetooth • The range limited only by the availability of the Wi-Fi network - Bluetooth/Wi-Fi gateway 	...

Searching and playback the records	...	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) Records playback from max. 16 channels in the same time
Network interface	...	2 x RJ-45 10/100/1000 Base-TX
Network functions	...	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users
Main features	<ul style="list-style-type: none"> • schedule, • timer, • manual watering (app or button), • delay after rain : 1 ... 7 days - the device will not turn on the sprinklers if it is raining, • remote access - Bluetooth/Wi-Fi gateway (included), • voice control • 2 x STATUS indicator • Low current consumption • Easy installation - the valve is mounted directly on the tap • 2 x 3/4" / 1/2" Adapter (included) 	...
Network protocols	...	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, RTSP, IEEE 802.1x, IPv6
ONVIF	...	✓
Housing	Plastic (ABS) + Nylon, UV-resistant, Waterproof	...
Default IP address	...	DHCP or 192.168.1.30
"Index of Protection"	IP55	...
Default admin user / password	...	admin / 123456
Color	Gray + Black	...
Mobile phones support	<ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS 	<ul style="list-style-type: none"> Port no.: 80 or access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	...	80

RTSP URL	...	rtsp://192.168.1.30:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.30:554/unicast/c1/s1/live - Sub stream
USB	...	2 x USB 2.0 1 x USB 3.0
Serial ports	...	RS-485
Alarm inputs / outputs	...	16 / 4
PTZ control	...	<ul style="list-style-type: none"> • PTZ Uniview cameras • RS-485 - PELCO-D/P and others
Motion Detection	...	✓
Intelligent image analysis	...	✓
Main features	...	<p>Functions implemented in cooperation between the recorder and cameras that support these functions</p> <ul style="list-style-type: none"> • Intelligent image analysis : crossing the line (tripwire), intrusion, entering the marked area, leaving the marked area, abandoned/missing object, scene changing, people counting, crowd gathering estimation, objects tracking • Smoke and temperature detection, fire detection • Motion detection with human/vehicle silhouette recognition • Intelligent recognition of the human figure and tracking the movement of a person • SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor vehicle • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • VIDEO signal loss alarm • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its
Mouse support	...	✓
IR remote controller in the set	...	—
Switch PoE	...	—
Power supply	4 x 1.5V, type AA/LR6/FR6 battery (not included)	12 V DC / 5 A (power adapter included)
Power consumption	...	≤ 20 W (without HDD)
Operation temp	4.5 °C ... 45 °C	-10 °C ... 55 °C

Weight	0.4 kg	3.16 kg
Dimensions	141 x 122 x 58 mm	440 x 352 x 48 mm
Supported languages	...	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovak, Italian
Manufacturer / Brand	...	UNIVIEW
Guarantee	2 years	3 years